View NSN Online: https://aerobasegroup.kr/nsn/8030-00-166-8808

Product ID:MICROPEEL MSDS Date:08/19/1987 FSC:8030 NIIN:00-166-8808 MSDS Number: BGVZQ === Responsible Party === Company Name: PYRAMID PLASTICS INC. Address:220 W. 5TH ST. City:HOPE State:AR ZIP:71801-5212 Info Phone Num:501-777-3251 Emergency Phone Num:501-777-3251 CAGE:86675 === Contractor Identification === Company Name: PYRAMID PLASTICS INC Address:220 W 5TH ST Box:City:HOPE State:AR ZIP:71801-5212 Country:US CAGE:86675 Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 70-75% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: PROPYLENE OXIDE (SARA III) CAS:75-56-9 RTECS #:TZ2975000 Fraction by Wt: 2% **OSHA PEL** 

:100 PPM ACGIH TLV:20 PPM; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:VINYL RESIN CAS:9010-76-8 Fraction by Wt: 18-22%

Ingred Name:CHROMIUM (III) OXIDE CAS:1308-38-9 RTECS #:GB6475000 Fraction by Wt: 4% OSHA PEL:0.5 MG/M3 (CR) ACGIH TLV:0.5 MG/M3 (CR); 8990

LD50 LC50 Mixture:2737 MG/KG(LD50 ORAL/RAT) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO H

ealth Hazards Acute and Chronic:EYES: SEVERE IRRITATION AND BLURRED VISION. SKIN: MODERATE IRRITATION AND DERMATITIS. SWALLOWED: NAUSEA AND VOMITING. INHALATION: DIZZINESS, NAUSEA, AND POSSIBLE UNCONSCIOUSNESS. PRE-EXISTING EYE, SKI N AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO PRODUCT.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS CHEMICAL IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure: EYES: SEVERE IRRITATION AND BLURRED VISION.

SKIN:MODERATE IRRITATION AND DERMATITIS. SWALLOWED: NAUSEA, AND POSSIBLE UNCONSCIOUSNESS. PRE-EXISTING EYE, SKIN, AND RESPIRATORY DISORDERS MAY BE AGGRAVATE D BY EXPOSURE TO PRODUCT.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF LIVER & KIDNEY PROBLEMS MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:INHALATION:REMOVE TO FRESH AIR. IF NOT BREATHING,GIVE CPR. CALL A PHYSICIAN. SKIN

WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CALL A PHYSICAIN. EYE: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALLA PHYSICAN. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE LARGE QUANTITIES OF WATER TO DRINK. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. CALL A PHYSICIAN.

Flash Point Method:TCC Flash Point:1F,-17C Lower Limits:2 Upper Limits:10 Extinguishing Medi a:CARBON DIOXIDE, ALCOHOL FOAM, DRY CHEMICAL. Fire Fighting Procedures:EVACUATE AREA, WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND SCBA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:MATERIAL IS HIGHLY VOLATILE. VAPORS ARE HEAVIER THAN AIR.

Spill Release Procedures:SMALL SPILL: ABSORB ON SAND OR OTHER NON-COMBUSTIBLE ABSORBANT. PLACE IN DISPOSAL CONTAINER. LARGE SPILL: EVACUATE ARE

A. VENTILATE AREA. ELIMINATE IGNITION SOURCES.
DIKE TO RETAIN SPILL. PICK UP FREE LIQUID WITH PUMP OR VACUUM.
ABSORB RESIDUE.
Neutralizing Agent:NONE RECOMMENDED.

Handling and Storage Precautions:STORE IN COOL,DRY AREA. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. PROTECT FROM PHYSICAL DAMAGE. KEEP AWAY FROM HEAT,FLAME OR SPARKS. Other Precautions:NONE

Respiratory Protection: SELECT NIOSH/MSHA APPROVED RESPIRATOR BASED UPON CONTAMINATION LEVELS FOUND IN THE WORK PLACE.

Ventilation:LOCAL AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN VAPOR AND MIST CONCENTRATIONS BELOW PELS EST. BY OSHA Protective Gloves:RUBBER (SOLVENT RESISTANT).

Eye Protection: SAFETY SPLASH GOGGLES.

Other Protective Equipment: EYE WASH STATION.

Work Hygienic Practices: WASH THOROUGHLY AFTER USE AND BEFORE EATING, DRINKING OR SMOKING, LAUND ER CONTAMINATED CLOHING BEFORE REUSE. Supplemental Safety and Health NONE.

HCC:F2 Boiling Pt:=71.1C, 160.F Vapor Pres:70 (MEK) Vapor Density:3 Spec Gravity:0.96 Evaporation Rate & amp; Reference:4 (BUTYL ACETATE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:GREEN LIQUID, FRAGRANT, MINT-LIKE, MODERATELY SHARP ODOR.

Percent Volatiles by Volume:90

S

tability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HIGH HEAT. Hazardous Decomposition Products:DURING COMBUSTION, CARBON MONOXIDE, CARBON DIOXIDE AND UNIDENTIFIED TOXIC FUMES AND/OR VAPORS.

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE AND LOCAL REGULATIONS AND LAWS. INCINERATION RECOMMENDED.

Disclaimer (provided with this information b

y the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.