

COASTAL EAGLE POINT OIL CO. -- REGULAR GASOLINE -- 9130-00-142-9457

=====
Product Identification
=====

Product ID:REGULAR GASOLINE

MSDS Date:08/07/1985

FSC:9130

NIIN:00-142-9457

MSDS Number: BGWXH

=== Responsible Party ===

Company Name:COASTAL EAGLE POINT OIL CO.

Address:9 GREENWAY PLAZA

City:HUSTON

State:TX

ZIP:77046

Info Phone Num:713-877-1400

Emergency Phone Num:713-877-1400

Preparer's Name:DEL

NO D. MALZAHN

CAGE:0BDU2

=== Contractor Identification ===

Company Name:COASTAL EAGLE POINT OIL CO, THE COSTAL CORP.

Address:9 GREENWAY PLAZA

City:HOUSTON

State:TX

ZIP:77046

Country:US

Phone:713-877-1400

CAGE:0BDU2

=====
Composition/Information on Ingredients
=====

Ingred Name:GASOLINE

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: 90-95%

OSHA PEL:300 PPM/500 STEL

ACGIH TLV:300 PPM/500STEL;9192

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 49

5F

Lower Limits:1.3

Upper Limits:7.6

Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM,WATER FOG. WATER MAY BE INEFFECTIVE,AS PRODUCT WILL FLOAT AND MAY SPREAD FIRE.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS IN ENCLOSED AREAS. WATER SPRAY MAY BE USED TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR,ACCUMULATING IN LOW AREAS,TRAVELING ALONG GROUND AND MAY FLASH BACK FROM DISTANT IGNITION SOURCE.

=====

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. ISOLATE AREA. USE PROTECTIVE EQUIPMENT AS NECESSARY. STOP LEAK AND CONTAIN SPILL. DIKE AS NEEDED TO KEEP SPILL FROM DRAINS,WATER WAYS ETC. WATER FOG MAY BE USED TO REDUCE V APOR & PERSONAL HAZARD. REPORT SPILL PER LAW.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,ISOLATED, WELL

VENTILATED AREA. KEEP IGNITION SOURCES AWAY. GROUND CONTAINERS TO PREVENT STATIC DISCHARGE DURING TRANSFERS.

Other Precautions:FIRE AND EXPLOSION ARE THE ACUTE HAZARDS OF THIS PRODUCT. TAKE EXTRAORDINARY STEP TO PREVENT THEM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF NEEDED,USE NIOSH/MSHA RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR PREFERRABLY,A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR OF SELF CONTAINED BREATHING APPARATUS.

Ventilation:USE EXPLOSION PROOF VENTILATION EQUIPMENT TO MAUNTAIN EXPOSURE BELOW PEL/TLV.

Protective Gloves:IMPERVIOUS RUBBER OR POLYMER.

Eye Protection:SAFETY GLASSES,OR SPLASH POLYMER.

Other Protective Equipment:SAFETY SHOWER/EYE WASH, WORK CLOTHING AS NEEDED TO PROTECT FROM PROLONGED/REPEATED CONTACT.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. MINIMIZE ALL CONTACT.

Supplemental Safety and Health

===== Physical/Chem

ical Properties =====

HCC:F2

Boiling Pt:B.P. Text:80-430F

Vapor Density:3.5

Spec Gravity:0.72 - 0.76

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR RED LIQUID;GASOLINE ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT,SPARKS AND OTHER IGNITION
SOURCES,VAPOR ACCUMULATIONS.

Hazardous Decomposition Products:CARBON DIOXID
E,CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE.LOCAL REGULATIONS.
PRODUCT QUALIFYS AS IGNITABLE WASTE AND CANNOT BE LANDFILLED. IF
RECOVERY OR RECYCLE ARE UNACCEPTABLE, INCINERATION MAY BE
ACCEPTABLE DISPOSAL METHOD.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of A
merica in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.