

OUTBOARD MARINE CORP -- 327361 GASKET ELIMINATOR/FLANGE SEALANT -- 5330-01-099-9384
===== Product Identification =====

Product ID:327361 GASKET ELIMINATOR/FLANGE SEALANT

MSDS Date:01/24/1983

FSC:5330

NIIN:01-099-9384

MSDS Number: BGXBZ

=== Responsible Party ===

Company Name:OUTBOARD MARINE CORP

Address:100 SEA HORSE DRIVE

City:WAUKEGAN

State:IL

ZIP:60085-2141

Country:US

Info Phone Num:312-689-5599

Emergency Phone Num:312-689-5599

CAGE:80256

=== Contractor Identification ===

Company Name:OUTBOARD MARINE CORP

Address:100 SEA HORSE DRIVE

Box:City:WAUKEGAN

State:IL

ZIP:60085-2141

Country:US

Phone:708-689-6200

CAGE:80256

===== Composition/Information on Ingredients =====

Ingred Name:POLYURETHANE METHACRYLATE RESINS

Fraction by Wt: 70-75%

Other REC Limits:NONE STATED

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:POLYGLYCOL DIMETHACRYLATES

Fraction by Wt:

5-10%
Other REC Limits:NONE STATED
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:SILICA (TYPE NOT SPECIFIED)
Fraction by Wt: 5-10%
Other REC Limits:NONE STATED
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ACRYLIC ACID (SARA III)
CAS:79-10-7
RTECS #:AS4375000
Fraction by Wt: 5%
OSHA PEL:S, 10 PPM
ACGIH TLV:S, 2 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ORGANIC HYDROPEROXIDE
Fraction by Wt: 3%
Other REC Limits:NONE STATED
OSHA PEL:N
ONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ETHYLENE GLYCOL (SARA III)
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 2%
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SULFIMIDE
Fraction by Wt: 1%
Other REC Limits:NONE STATED
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 1%
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EP

A Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HYDRAZIDE
Fraction by Wt: 1%
Other REC Limits:NONE STATED
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:HYDROQUINONE (SARA III)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 7% PPM
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO
OSHA:NO
Health Hazards Acute and Chronic:HIGH LEVELS OF ACRYLIC ACID CAUSE NOSE
AND THROAT IRRITATION. SEALANT IS AN EYE IRRITANT. MAY CAUSE
DERMATITIS ON PROLONGED CONTACT IN SENSITIVE INDIVIDUALS.
Effects of Overexposure:SEE "HEALTH HAZARDS"

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.SEE DOCTOR.
SKIN:WASH WITH SOAP AND WATER; INHALATION: REMOVE VICTIM TO FRESH
AIR; INGESTION:KEEP CALM AND OBTA
IN MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:>200F/93.3C
Extinguishing Media:CARBON DIOXIDE,FOAM OR DRY CHEMICAL.
Fire Fighting Procedures:NONE STATED
Unusual Fire/Explosion Hazard:NONE STATED

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP AS MUCH AS POSSIBLE AND SCORE IN A
PARTIALLY-FILLED CLOSED CONTAINER UNTIL DISPOSAL. RESIDUES MAY BE
CLEANED WIT

H SOLVENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED PLACE,AWAY FROM HEAT,IGNITION SOURCES AND INCOMPATIBLE MATERIALS.KEEP CONTAINERS CLOSED WHEN NOT IN USE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE USUALLY REQUIRED.

Ventilation:SUFFICIENT MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective

Gloves:RUBBER

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.

Work Hygienic Practices:AVOID CONTACT WITH EYES & SKIN.DO NOT BREATHE VAPORS.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>300F/1489C

Vapor Pres:5

Spec Gravity:1.1

Solubility in Water:LOW

Appearance and Odor:RED GEL WITH MILD ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WILL

ATTACK SOME THERMOPLASTICS.

Stability Condition to Avoid:NONE STATED

Hazardous Decomposition Products:NONE STATED

=====
===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATE FOLLOWING ALL APPLICABLE FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in

no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.