

JETCO INC. -- JET-START FAST FLASH FUEL,NO. 60 #1224 -- 2910-00-646-9727

=====
Product Identification
=====

Product ID:JET-START FAST FLASH FUEL,NO. 60 #1224

MSDS Date:11/05/1986

FSC:2910

NIIN:00-646-9727

MSDS Number: BGXHK

=== Responsible Party ===

Company Name:JETCO INC.

Address:3920 W. CLARENDON AVE

City:PHOENIX

State:AZ

ZIP:85019

Country:US

Info Phone Num:602-269-5971

Emergency Phone Num:N/K

800-424-9300 (CHEMTREC)

CAGE:KO619

=== Contractor Identification ===

Company Name:JETCO INC

Address:3920 W CLARENDON AVE

Box:City:PHOENIX

State:AZ

ZIP:85019-3608

Country:US

Phone:602-269-5971

CAGE:50999

Company Name:JETCO INC.

Address:3920 W. CLARENDON AVE.

Box:City:PHOENIX

State:AZ

ZIP:85001

Country:US

Phone:602-269-5971

CAGE:KO619

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ETHER (SARA III)

CAS:60-29-7

RTECS #:KI5775000

Fraction by Wt: 87%.

OSHA PE

L:400 PPM/500 STEL
ACGIH TLV:400PPM/500STEL; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingrid Name:PROPELLANTS(AS PRESSURIZING GASES, INERT IN NATURE & DONOT
ADD TO HAZARDOUS QUALITY OF MIX) "TRADE SECRET"
Fraction by Wt: 13%

=====
Hazards Identification
=====

LD50 LC50 Mixture:LDLO(HUMAN)=420MG/KG-ORAL
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGE

D EXPOSURE MAY RESULT IN
RESPIRATORY FAILURE & DEATH. TOXICITY DATA, ORAL: RAT LD50=1.7
G/KG; HUMAN LDLO=420 MG/KG. SKIN: NONE FOUND; INHAL: RAT
LC50=73,000 PPM/150 MIN.

Effects of Overexposure:INHAL:VAPORS & MISTS IRRITATE RESPIRATORY
TRACT. AT HIGH CONC., HEADACHE,NAUSEA,VOMITING, & COMA AT VERY
HI-CONC OR PROLONGED EXPOSURE MAY CAUSE UNCONSCIOUSNESS OR DEATH.
EYES: VAPORS IRRITATE, LIQUID WILL IRRITATE AND MAY BURN;
SKIN:IRRITATES AFTER PROLONGED CONTACT & MAY BUR

N; ING: IN LARGE
QTY,HEADACHE,STUPOR

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS OR EYE
PROBLEMS OR IMPAIRED LIVER,KIDNEY OR RESPIRATORY FUNCTION IN
SUSCEPTIBLE PERSONS. ALCOHOLIC BEVERAGE CONSUMPTION CAN ENHANCE
TOXIC EFFECTS OF THIS SUBSTANCE.

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT
BREATHING. GET IMMEDIATE MED ATTN.; EYE CONTACT:FLUSH W/ LOTS OF
RU

NNING WATER FOR 15 MIN. LIFTING UPPER & LOWER EYELIDS
OCCASIONALLY, GET IMMEDIATE MED ATTN.; SKIN: WASH W/ LOTS OF SOAP
& WATER. REMOVE CONTAMIN CLOTHING & SHOES. WASH BEFORE REUSE. GET
MED ATTN IF IRRITAT AFTER WASHING. INGEST:IF CONSCIOUS,INDUCE
VOMITING.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:-49F/-45C
Lower Limits:1.85
Upper Limits:48.
Extinguishing Media:WATER, ALCOHOL FOAM, CARBON DIOXIDE, OR DRY
CHEMIC

ALS.

Fire Fighting Procedures:AVOID FLAMES OR SPARKS; FLOOD AREA W/ WATER & ALLOW MIX TO EVAPORATE TO OUTSIDE AIR.

Unusual Fire/Explosion Hazard:NOT MISCIBLE IN WATER,BUT SOLUBLE TO 6.5%. BECAUSE OF LOW BOILING PT, BEST TO TREAT AS A GAS. EXERCISE CAUTION TO AVOID CONTACT BTWN VAPOR & HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL IGNITION SOURCES & ENSURE THAT ALL HANDLING EQUIPMENT IS ELECTRICALLY GROUNDED.

LARGE SPILLS:N/A;

SMALL SPILLS:MOP OR WIPE UP & DISPOSE OF IN DOT-APPROVED WASTE CONTAINER. KEEP OUT OF SEWERS, STORM DRAINS, SURFACE WATERS, & SOILS.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE CAREFULLY IN OPEN, WELL-VENTILATED AREAS. STORE AWAY FROM HEAT AND/OR ALL IGNITION SOURCES, AT TEMPS LOWER THAN 122F/50C.

Other Precautions:AN EYEWASH & SOURCE OF RUNNING WATER SHOULD BE NEARBY & READY FOR USE

CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH THIS SUBSTANCE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS DO NOT MAINTAIN INHALATION EXPOSURE BELOW PEL/TLV, USE NIOSH/MSHA APPROVED RESPIRATORS AS PER CURRENT 29CFR1910.134, INSTRUCTIONS/WARNINGS & NIOSH RESPIRATOR DECISION LOGIC-PUB #87.108;

Ventilation:PROVIDE SUFFICIENT GENERAL/LOCAL EXHAUST VENTILATION IN PATTERN/VOLUME TO CONTROL INHALATION EXPOSURE BELOW PEL/TLV.

Protective Gloves:NITRILE OR IMPERVIOUS TYPE FOR TASK.

Eye Protection:CHEMICAL GOGGLES OR AS APPROPRIATE.

Other Protective Equipment:AS REQUIRED FOR TASK AT HAND TO MINIMIZE EXPOSURE.

Work Hygienic Practices:CYLINDERS THAT CONTAIN THIS ENGINE STARTING FLUID ARE TO BE HANDLED CAREFULLY IN OPEN, SPARK-FREE, WELL VENTILATED AREA.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:G2

Boiling Pt:B.P. Text:94F/35C

Melt/Freeze Pt:M.P/F.P Text:-177F/-116C
Vapor Pres:442 @ 68F
Vapor Density:2.56
Spec Gravity:0.710 @ 77F
Evaporation Rate & Reference:(BUTYL ACETATE=1),6.9
Solubility in Water:65 GMS/LITER @ 68F
Appearance and Odor:COLORLESS LIQUID W/SWEET PUNGENT ODOR.
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO
OXIDIZING MATERIALS.
Stability Condition to Avoid:CONDITIONS FAVORING PEROXIDE FORMATION,
HEAT, & IGNITION SOURCES.
Hazardous Decomposition Products:OXIDES OF CARBON (CO, & CO*2) &
PEROXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF CONTAMINATED PRODUCT & MATERIAL USED
IN CLEANING UP SPILLS OR LEAKS IN A MANNER FOR THIS MATERIAL.
CONSULT APPROPRIATE FED, STATE & LOCAL REGULATORY AGENCIES TO
ASCERTAIN PROPER DISPOSAL PROCEDURES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.