

DOW CORNING CORPORATION -- 93-006 AEROSPACE SEALANT -- 8030-00-115-1832

=====
Product Identification
=====

Product ID:93-006 AEROSPACE SEALANT

MSDS Date:10/16/1985

FSC:8030

NIIN:00-115-1832

MSDS Number: BGZDG

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:3901 SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Info Phone Num:(517) 496-5900

Emergency Phone Num:(517) 496-590

0

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICONE

Ingred Name:ZINC COMPOUND

Fraction by Wt: 25%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:N

O

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: TEMPORARY DISCOMFORT. SKIN: SLIGHT IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYE: TEMPORARY DISCOMFORT. SKIN: SLIGHT IRRITATION.

Medical Cond Aggravated by Exposure:ALLERGIC CONDITIONS IN CERTAIN PEOPLE.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: WIPE OFF & FLUSH W/WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>200F

Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM, OTHER.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT & CONTAIN FOR SALVAGE/DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage P

recations:STORE 300F

Vapor Pres: