

CHEMRAY COATING CORP -- ENAMEL/ALKYD/GLOSS/TT-C-489G, RED 11136-1 -- 8010-00-527-3198
===== Product Identification =====

Product ID:ENAMEL/ALKYD/GLOSS/TT-C-489G, RED 11136-1
MSDS Date:06/21/1988
FSC:8010
NIIN:00-527-3198
MSDS Number: BGZZX
=== Responsible Party ===
Company Name:CHEMRAY COATING CORP
Address:209 N MICHIGAN AVE
City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Info Phone Num:201-245-111

1
Emergency Phone Num:201-245-1111
CAGE:33832
=== Contractor Identification ===
Company Name:CHEMRAY COATING CORP
Address:209 N MICHIGAN AVE
Box:City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:201-245-1111
CAGE:33832

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:8032-32-4
RTECS #:OI6180000
Other REC Limits:STEL 400 PPM
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

Ingred Name:MOLYBDATE ORANGE
CAS:12656-85-8
RTECS #:QA46600

00
Fraction by Wt: 2%
Other REC Limits:STEL 10 MG/CUM
OSHA PEL:5 MG/CUM
ACGIH TLV:5 MG/CUM

Ingrid Name:VOL ORGANIC CMPD: (4.10 LBS/GAL)
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION TO RESPIRATORY TRACT, HEADACHES & DIZZINESS. EYE/SKIN: IRRITATION. INGESTION: MAY BE HARMFUL/FATAL.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: IRRITATION OF THE RESPIRATORY TRACT, HEADACHES, DIZZINESS, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION: MAY BE HARMFUL/FATAL.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH W/WATER 15 MINUTES/UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS CALL PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR, CALL PHYSICIAN. INGESTION: DON'T INDUCE VOMITING, CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:103F
Lower Limits:0.7%
Upper Limits:0.9%
Extinguishing Media:CO2, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED CONTAINERS W/WATER SPRAY, AVOID BREATHING VAPOR/FUMES.
Unusual Fire/Explosion Hazard:IF LEAD/SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE

VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT SAND, EARTH, SAWDUST, TO SPILL. VENTILATE AREA. KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSES BY DIKING.

===== Handling and Storage =====

Handling and Storage Precautions: WASH HAND THOROUGHLY AFTER USE & KEEP CONTAINER CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER/SUPPLIED AIR RESPIRATORY IN CONFINED AREA.

Ventilation: PROVIDE LOCAL EXHAUST/MECHANICAL VENTILATION FOR FACE VELOCITY 60FPM/EXPLOSION-PROOF EQUIPMENT.

Protective Gloves: CHEMICAL RESISTANT

Eye Protection: GOGGLES, FACE SHIELD

Other Protective Equipment: USE CHEM. RESISTANT APRON, OTHER CLOTHING.

Work Hygienic Practices: WASH HAND THOROUGHLY AFTER USE & KEEP CONTAINER

CLOSED WHE NOT IN USE. REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt: B.P. Text: 308F

Melt/Freeze Pt: M.P/F.P Text: