

BORDEN, INC -- KRYLON SPRAY PRIMER; RUDDY BROWN: 1318 -- 8010-00-616-9181
===== Product Identification =====

Product ID:KRYLON SPRAY PRIMER; RUDDY BROWN: 1318

MSDS Date:06/30/1986

FSC:8010

NIIN:00-616-9181

MSDS Number: BHB BB

=== Responsible Party ===

Company Name:BORDEN, INC

Address:180 EAST BROAD STREET

City:COLUMBUS

State:OH

ZIP:43215

Info Phone Num:(800) 848-9400

Emergency Phone Num:(614) 431-

6600

CAGE:FO346

=== Contractor Identification ===

Company Name:ARABOL DEPT BORDEN CHEMICAL DIV OF BORDEN INC

Address:180 E BROAD ST

Box:City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Phone:614-225-6124

CAGE:84163

Company Name:BORDEN, INC

Address:180 EAST BROAD STREET

City:COLUMBUS

State:OH

ZIP:43215

Phone:(614) 431-6600

CAGE:FO346

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 33%

Other REC Li

imits:590 MG/CUM
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 16-17%
Other REC Limits:1800 MG/CUM
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 1-2%
Other REC Limits:50 PPM
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
R
TECS #:XS5250000
Fraction by Wt: 23-27%
Other REC Limits:100 PPM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 4-6%
Other REC Limits:STEL 400 PPM
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSH

A:NO

Health Hazards Acute and Chronic:INHALATION: CNS DEPRESSION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS & ASPHYXIATION, CYANOISIS, RESPIRATORY DISTRESS, DROWSINESS, LIVER & KIDNEY DAMAGE. OVEREXPOSURE W/ PERMANENT BRAIN/N ERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING/INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: CNS DEPRESSION, HEADACHE, DIZZINESS, NAUSEA, VO
MITING, UNCONSCIOUSNESS, ASPHYXIATION,
CYANOSIS, RESPIRATORY DISTRESS, DROWSINESS, LIVER & KIDNEY DAMAGE, IRRITATION OF NOSE, THROAT, LUNGS, S KIN & EYES.

=====
First Aid Measures
=====

First Aid:INGESTION: DON'T INDUCE VOMITING, CALL PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL PHYSICIAN. SKIN: FLUSH W/ WATER. EYE: FLUSH W/PLENTY OF WATER FORAT LE
AST 15 MINS. EYELIDS
SHOULD BE HELD APART DURING IRRIGATION TO INSURE WATER CONTACT W/ENTIRE SURFACE OF EYES/LIDS. CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:FLAMMABLE
Extinguishing Media:USE DRY CHEMICAL, FOAM OR CO2.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL. DON'T SPRAY NEAR OPEN FLAME.
Unusual Fire/Explosion Hazard:EXPOSURE TO HIGH TEMP MAY CAUSE BURSTING.

AVOID RADIATORS, STOVES, DIRECT SUNLIGHT, OR OTHER HEAT SOURCE.
DON'T PUNCTURE OR INCINERATE CONTAINER.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:MAY CONTAIN EXPLOSIVE VAPORS. DON'T

CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY.

Other Precautions: DON'T STORE AT TEMPERATURES >120F. AVOID BREATHING VAPOR/MISTS. USE WITH ADEQUATE VENTILATION. AVOID CONTACT W/SKIN & EYES. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT.

Ventilation: PROVIDE

SUFFICIENT LOCAL EXHAUST VENTILATION TO KEEP AIR

Spec Gravity: