

PRATT AND LAMBERT INC -- LACQUER C/N GLOSS 01 WHITE 17875 ID786716 -- 8010-00-257-5377

=====  
Product Identification  
=====

Product ID:LACQUER C/N GLOSS 01 WHITE 17875 ID786716  
MSDS Date:12/15/1988  
FSC:8010  
NIIN:00-257-5377  
MSDS Number: BHBXC  
=== Responsible Party ===  
Company Name:PRATT AND LAMBERT INC  
Address:16116 E 13TH ST  
Box:2153  
City:WICHITA  
State:KS  
ZIP:67201  
Country:US  
Info Phone Num:316-73  
3-1361  
Emergency Phone Num:716-873-6000 DOT EMER 8002553924  
Preparer's Name:W.A. ELLISON  
CAGE:61196

==== Contractor Identification ====

Company Name:PRATT AND LAMBERT INC  
Box:6027  
City:CLEVELAND  
State:OH  
ZIP:44101-1027  
Country:US  
Phone:216-566-2902  
CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOBUTYL ACETATE (SARA III)  
CAS:110-19-0  
RTECS #:AI4025000  
OSHA PEL:150 PPM  
ACGIH TLV:150 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISO

PROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE  
CAS:9004-70-0  
RTECS #:QW0970000  
OSHA PEL:NONE ESTABLISHED  
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:NAPHTA (PETR  
OLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:DE3030000  
OSHA PEL:100 PPM

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA  
III)  
CAS:117-81-7  
RTECS #:TI0350000  
OSHA PEL:5 MG/M3/10 STEL  
ACGIH TLV:5 MG/M3; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:N-HEPTANE  
CAS:142-82-5  
RTECS #:MI7700000  
OSHA PEL:500 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:VOL ORGANIC CMPD 5.0 LB/GL LESS WATER & NPRS\* 600 G/L LESS  
WATER VOC 20.6 LB/GAL SOLIDS 2472 G/L SO

LIDS CALCULATED  
RTECS #:9999999VO

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:NO

Health Hazards Acute and Chronic:SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION,NAUSEA AND VOMITING. INHALATION MAY CAUSE NOSE OR THROAT IRRITATION. EYE-MAY CAUSE EYE IRRITATION. SKIN PRIMARY SKIN IRRITANT. MAY CAUSE DEFATTING AND IRRITATION OF THE SKIN. HIGH CONCENTRATION

S MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS A POTENTIAL CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM.

Effects of Overexposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE C ONTENTS MAY BE HARMFUL OR FATAL.

=====  
First Aid Measure  
=====

S =====

First Aid:SWALLOWING:DO NOT INDUCE VOMITING. GET MED ATTN;

INHALATION:REMOVE TO FRESH AIR IMMED AND GET MED ATTN. EYE:FLUSH WITH LARGE AMOUNTS OF WATER AT LEAST 15 MIN. GET MED ATTN.

SKIN:FLUSH THE CONTAMINATED AREA WITH WATER. REMOVE CLOTHING.CONSULT A PHYSICIAN. NOTE TO PHYSICIAN ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS

=====  
Fire Fightin  
=====

g Measures =====

Flash Point:20F/-6.67C

Extinguishing Media:CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WTR MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS. IF WTR USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:DURING EMERGENCY COND OVEREXP TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT.OBT

AIN MEDICAL ATTN;WARNING:FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. USE ONLY NON-SPARKING TOOLS.DIKE WITH INERT MATERIAL.PUT IN METAL CONTAINERS FOR DISPOSAL. PREVENT CONTAMINATION OF SEWERS,STREAMS, AND GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29C FR1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. DO NOT REUSE CONTAINERS.DO NOT WELD/BRAZE/CUT ON CONTAINERS.NEVER USE PRESSURE TO EMPTY. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED VENTILATION A NIOSH CHEMICAL RESPIRATOR MAY BE REQUIRED. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIR RESPIRATOR. REFER TO OSHA 29 CFR1910.134 AND RESPIRATORY PROTECTION A MANUAL AND GUIDELINE, AMERICAN HYGIENE ASSOC.

Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO MAINTAIN CONCENTRATIONS.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health  
NONE LISTED.

===== Physical/Chemical Properties =====

HCC:F2

Boiling

Point:Boiling Point:181F/302F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE SMOKE,CARBON MONOXIDE & CARBON DIOXIDE. IN ADDITION

N OXIDES OF  
NITROGEN MAY BE GEN.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT,SPARKS AND  
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW FEDERAL,STATE AND LOCAL  
LAWS.INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED  
CONTAINERS. MATERIAL TO BE DISPOSED OF IN A HAZARDOUS WASTE  
LANDFILL.RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.