

PHILLIPS 66 COMPANY -- TOLUENE,A42444,A42500 -- 6810-00-411-4192

=====
Product Identification
=====

Product ID:TOLUENE,A42444,A42500

MSDS Date:04/27/1989

FSC:6810

NIIN:00-411-4192

MSDS Number: BHBYQ

=== Responsible Party ===

Company Name:PHILLIPS 66 COMPANY

City:BARTLESVILLE,

State:OK

ZIP:74004

Country:US

Info Phone Num:918-661-8327

Emergency Phone Num:918-661-3865/8118

CAGE:46935

=== Contractor I

dentification ===

Company Name:EAGLE MILL SUPPLY CO INC

Address:2819 W 7TH STREET

Box:City:TEXARKANA

State:TX

ZIP:75501-6423

Country:US

Phone:214-794-0800

CAGE:2V894

Company Name:PHILLIPS PETROLEUM CO

Address:613 ADAMS

Box:City:BARTLESVILLE

State:OK

ZIP:74004

Country:US

Phone:800-234-6603

CAGE:46935

Company Name:SHAPE PRODUCTS

Address:1127 57TH AVE.

Box:City:OAKLAND

State:CA

ZIP:94621-4427

Country:US

Phone:510-534-1186 OR 800-444-0015

CAGE:3D869

=====
Composition/Information on Ingredi

ents =====

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 99.95%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE;IRRITATION OF
EYES,SKIN,RESPIRATORY AND G.I.TRACT;CNS EFFECTS LIKE
HEADACH
E,DIZZINESS,CNS DEPRESSION NAUSEA. CHRONIC:DRYING OF
SKIN,DERMATTIS.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:SEE HEALTH HAZARDS DATA.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:40.0F,4.4C
Autoignition Temp:Autoignition Temp Text:TCC
Lower Limits:1.2
Upper Limits:7.1
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST WHEN EXPOSED TO HEAT
OF F

IRE. CARBON OXIDES FORMED WHEN BURNED.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBANT. PUT IN DISPOSAL CONTAINER. REMOVE RESIDUE WITH WATER. LARGE SPILL: EVACUATE AND VENTILATE AREA. IF POSSIBLE, STOP LEAK. DIKE TO RETAIN RUN OFF. VACUUM UP FREE LIQUID. ABSORB/WASH RESIDUE.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. FOR INDUSTRIAL USE ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory

Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:NEOPRENE, NITRILE, VPC OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTION
AL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:F2

Boil

ing Pt:B.P. Text:231F,111C

Vapor Pres:1.03

Vapor Density:3.1

Spec Gravity:0.872

Evaporation Rate & Reference:>1.0(N-BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR LIQUID,MILD AROMATIC ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS,OXYGEN.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OPEN FLAMES

Hazardous Decomposition Products:

CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL
APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be
accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.