

PRATT & LAMBERT, INC. -- LACQUER C/N GLOSS 01 WHITE 17875 ID786716 -- 8010-00-242-6315
===== Product Identification =====

Product ID:LACQUER C/N GLOSS 01 WHITE 17875 ID786716

MSDS Date:12/15/1988

FSC:8010

NIIN:00-242-6315

MSDS Number: BHCBD

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A.

ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPRO

PYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
OSHA PEL:100 PPM

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:VOL ORGANIC CMPD 5.0 LB/GL LESS WATER & NPRS* 600 G/L LESS WATER VOC 20.6 LB/GAL SOLIDS 2472 G/L SOLID

S CALCULATED
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:SWALLOWING/GASTROINTESTINAL
IRRITATION,NAUSEA,VOMITING. INHALATION/MAY CAUSE NOSE,THROAT IRRIT.
HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM
DEPRESSION. EYE/IRRITATION. SKIN/MAY CAUSE DE FATTING, IRRITATION
OF THE SKIN.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL)PHTHALATE I
S LISTED AS A

POTENTIAL CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM.

Effects of Overexposure:REPEATED OVEREXPOSURE TO TOLUENE MAY CAUSE
LIVER DAMAGE. PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO
SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.
DELIBERATELY CONCENTRATING AND INH ALING THE CONTENTS MAY BE
HARMFUL OR FATAL. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEM
PNEUMONITIS CAN BE FATAL.

=====
First Aid Measures
=====

First Aid:SWALLOWING/DO NOT INDUCE VOMITING. GET MED ATTN:
INHALATION/GET FRESH AIR IMMED.IF BREATHING HAS STOPPED,GIVE
ARTIFICIAL RESPIRATION. GET MED ATTN: EYE/FLUSH WITH LG AMT OF
WATER FOR 15 MIN. GET MED A TTN. SKIN/FLUSH THE CONTAMINATED AREA
W/ LG AMT OF WATER.REMOVE CONTAMINATED CLOTHING.CONSULT A DR. NOTE
TO DR. ANY TREATMENT FOR OVEREXP S/B DIRECTED AT THE CONTROL OF
SYMPTOMS & CLINICAL CONDITIONS.

=====
Fire Fighting Measures
=====

Flash Point:20F -6.67C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM
IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
MAY BE INEFFECTIVE BUT CAN BE USED TO COOL EXPOSED CONTAINERS. IF
WATER IS USED, FOG NOZZLES ARE PREFERRABLE.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PROD MAY
CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMED APPARENT. OBTAIN
MEDICAL ATTN. WARNING! FLA

MMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL IGNITION SOURCES.DIKE & CONTAIN SPILL WITH INERT MATERIAL.USE COVERED METAL CONT FOR RECOVERY OR DISPOSAL.USE ONLY NON-SPARKING TOOLS.DONT CONTAMINATE SEWERS, STREAMS AND GROUNDWATER.KEEP SPE CTATORS AWAY.WEAR APPROPRIATE RESPIRATORS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARG E

QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:DO NOT REUSE CONTAINERS. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD/BRAZE/CUT ON EMPTY CONT. NEVER USE PRESSURE TO EMPTY.DRUM NOT A PRESSURE VESSEL. CLOSE AFTER E ACH USE.DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED AREAS A NIOSH RESPIRATOR MAY BE REQUIRED. CONFINED AREAS A NIOSH/MSHA

APPROVED AIR SUPPLIED

RESPIRATOR. SEE OSHA 29CFR1910.134. RESPIRATORY PROTECTION AND RESPIRATORY PROTECTION MANUAL A ND GUIDELINE, AMER IND HYGIENE ASSOC.

Ventilation:GENERAL AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO MAINTAIN CONCENTRATIONS OF SUBSTANCES.

Protective Gloves:IMPERMEABLE GLOVES.

Eye Protection:SAFETY SPECTACLES.

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health
NONE LISTED.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:180F/302F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE SM

OKE,CARBON MONOXIDE AND CARBON DIOXIDE. OXIDES OF NITROGEN MAY BE GENERATED.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT,SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. DISPOSE IAW FEDERAL,STATE AND LOCAL LAWS/REGULATIONS. RCRA CLAS SIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.