

EXXON CO. -- 1209 TURBINE LUBRICANT -- 9150-01-263-7239

===== Product Identification =====

Product ID:1209 TURBINE LUBRICANT

MSDS Date:10/24/1988

FSC:9150

NIIN:01-263-7239

MSDS Number: BHCPT

=== Responsible Party ===

Company Name:EXXON CO.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Emergency Phone Num:713-6563424

CAGE:NO321

=== Contractor Identification ===

Company Name:EXXON CO.

Box:2180

City:

HOUSTON

State:TX

ZIP:77252-2180

CAGE:NO321

Company Name:EXXON COMPANY U.S.A.

Address:Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OIL BASE STOCK.

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: >95%

Other REC Li

imits:ACGIH STEL 10 MG/M3  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:TRICRESYL PHOSPHATE \*NOTE\* THE LIMITS LISTED ARE FOR THE  
ORTHO ISOMER. MFR LISTS INGREDIENT AS"MIXTURE".

CAS:1330-78-5

RTECS #:TD0175000

Fraction by Wt: 500F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM,WATER FOG.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE  
WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Haz

ard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER AS LIQUID IF PRACTICAL,AND ADSORB  
REMAINDER WITH SAND OR OTHER MATERIAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL VENTILATED  
AREA.

Other Precautions:APPLY ALL PRECAUTIONS TO EMPTY CONTAINERS AS WELL AS  
FULL ONES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE EXPECTED TO BE NECESSARY. USE NIOSH/MSHA  
RESPIRATORS IF PRODUCT SHOULD BE VAPORIZED OR MISTED.

Ventilation:NORMAL ROOM VENTILATION. USE LOCAL EXHAUST TO REMOVE ANY  
VAPORS.OR MISTS GENERATED.

Protective Gloves:RUBBER,PLASTIC, OTHER IMPERVIOUS.

Eye Protection:SAFETY GLASSES.OR SPLASH GOGGLES/

Other Protective Equipment:IMPERVIOUS CLOTHING AS REQUIRED TO PREVENT  
PROLONGED/REPEATED CONTACT.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE

PRACTICE. AVOID

UNNECESSARY CONTACT. DO NOT BREATHE MIST OR VAPORS.

Supplemental Safety and Health

PRODUCT CODE 341209-01209.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:555F/291C

Melt/Freeze Pt:M.P/F.P Text:14F/-10C

Vapor Pres:5

Spec Gravity:0.88

pH:NEUTRL

Viscosity:77 CST @ 40C

Evaporation Rate & Reference: