View NSN Online: https://aerobasegroup.kr/nsn/9150-01-263-7239

EXXON CO. -- 1209 TURBINE LUBRICANT -- 9150-01-263-7239

Product ID:1209 TURBINE LUBRICANT

MSDS Date:10/24/1988

FSC:9150

NIIN:01-263-7239

MSDS Number: BHCPT === Responsible Party === Company Name: EXXON CO.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Emergency Phone Num:713-6563424

CAGE:NO321

=== Contractor Identification ===

Company Name: EXXON CO.

Box:2180

City:

HOUSTON

State:TX

ZIP:77252-2180

CAGE:NO321

Company Name: EXXON COMPANY U.S.A.

Address:Box:2180 City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name: OCTAGON PROCESS INC.

Address:596 RIVER ROAD Box:City:EDGEWATER

State:NJ ZIP:07020 Country:US

Phone:201-945-9400

CAGE:82925

======= Composition/Information on Ingredients ========

Ingred Name: LUBRICATING OIL BASE STOCK.

CAS:64742-54-7 RTECS #:PY8035500 Fraction by Wt: >95%

Other REC Li

mits:ACGIH STEL 10 MG/M3 OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:TRICRESYL PHOSPHATE *NOTE* THE LIMITS LISTED ARE FOR THE ORTHO ISOMER. MFR LISTS INGREDIENT AS"MIXTURE".

CAS:1330-78-5

RTECS #:TD0175000 Fraction by Wt: 500F Lower Limits:0.9 Upper Limits:7.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG.

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Haz

ard:NONE

========= Accidental Release Measures =============

Spill Release Procedures:RECOVER AS LIQUID IF PRACTICAL, AND ADSORB REMAINDER WITH SAND OR OTHER MATERIAL.

Neutralizing Agent:NONE

=========== Handling and Storage =============

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA.

Other Precautions: APPLY ALL PRECAUTIONS TO EMPTY CONTAINERS AS WELL AS FULL ONES.

====== Exposure Controls/Personal Protection

Respiratory Protection: NONE EXPECTED TO BE NECESSARY. USE NIOSH/MSHA RESPIRATORS IF PRODUCT SHOULD BE VAPORIZED OR MISTED.

Ventilation: NORMAL ROOM VENTILATION. USE LOCAL EXHAUST TO REMOVE ANY VAPORS.OR MISTS GENERATED.

Protective Gloves: RUBBER, PLASTIC, OTHER IMPERVIOUS.

Eye Protection: SAFETY GLASSES.OR SPLASH GOGGLES/

Other Protective Equipment:IMPERVIOUS CLOTHING AS REQUIRED TO PREVENT PROLONGED/REPEATED CONTACT.

Work Hygienic Practices: USE GOOD INDUSTRIAL HYGIENE

PRACTICE. AVOID
UNNECESSARY CONTACT. DO NOT BREATHE MIST OR VAPORS.
Supplemental Safety and Health
PRODUCT CODE 341209-01209.

======== Physical/Chemical Properties ==========

HCC:V6

Boiling Pt:B.P. Text:555F/291C
Melt/Freeze Pt:M.P/F.P Text:14F/-10C
Vapor Pres:5
Spec Gravity:0.88
pH:NEUTRL
Viscosity:77 CST @ 40C

Evaporation Rate & Deference: