

THE FLAMEMASTER CORPORATION -- E-400 (TSC) TOP COAT SEALER PE-400 -- 8030-00-009-5032

===== Product Identification =====

Product ID:E-400 (TSC) TOP COAT SEALER PE-400

MSDS Date:10/24/1986

FSC:8030

NIIN:00-009-5032

Kit Part:Y

MSDS Number: BHCWN

=== Responsible Party ===

Company Name:THE FLAMEMASTER CORPORATION

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Phone Num:81

8-982-1650

Emergency Phone Num:818-982-1650

Preparer's Name:SAMUEL L. ENGEL, SR.

CAGE:6N186

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

Company Name:THE FLAMEMASTER CORPORATION

CAGE:6N186

===== Composition/Information on Ingredients =====

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER POLYMER

(EPOXY RESIN)

CAS:25068-38-6

F

raction by Wt: 21-22%

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 15-18%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:ALIPHATIC POLYAMIDOAMIDE

CAS:68410-23-1

Fraction by Wt: 10-12%

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN
1% CRYSTALLINE SILICA

CAS:61790-53-2

RTECS #:HL8600000

Fraction by Wt: 0-10%

OSHA PEL:20 MPPCF

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TITANIUM DIOXIDE

CAS:134

63-67-7

RTECS #:XS2275000

Fraction by Wt: 7-9%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER

CAS:107-98-2

RTECS #:UB7700000

Fraction by Wt: 6-7%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 9-10%

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name:ISPORONANOL

RTECS #:NT8600000

Fraction by Wt: 4-5%

ACGIH TLV:400 PPM

Ingred Name:N-BUTYL ALCOHOL (SA

RA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 9-10%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SENSITIZER - MAY CAUSE ALLERGIC SKIN
REACTION WHICH CAN BE SEVERE IN CERTAIN IN-DIVIDUALS
Effects of Overexposure:SENSITIZER - MAY CAUS
E ALLERGIC SKIN REACTION
WHICH CAN BE SEVERE IN CERTAIN INDIVIDUALS

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH MILD SOAP AND WATER. EYES:
IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. CONSULT
A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:40 F 4.44 C
Lower Limits:0.9
Upper Limits:15.8
Extinguishing Media:CO2, FOAM, DRY CHEMICAL, AND/OR WA
TER SPRAY
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY
BE TOXIC

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF HEAT AND OPEN FLAME.
DIKE SPILL. ABSORB WITH INERT MATERIAL. SHOVEL INTO A CLOSABLE
CONTAINER FOR DISPOSAL

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMA

BLE LIQUID. STORE IN COOL DRY
PLACE AWAY FROM HEAT AND OPEN FLAME
Other Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING,
DRINKING OR SMOKING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PAPROV/CCRFOV
Ventilation:GOOD MECHANICAL VENTILATION WITH LOCAL EXHAUST
Protective Gloves:NEOPRENE
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:SKIN CREAMS
Work Hygienic Practices:GOOD GENERAL HYGIENE PRACTICES
Supplementa
I Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:231 F
Decomp Temp:Decomp Text:NA
Vapor Pres:13.72MM
Vapor Density:3.64 AIR
Spec Gravity:1.2
pH:NA
Evaporation Rate & Reference:..93
Solubility in Water:INSOLUBLE
Appearance and Odor:CLEAR, WHITE, GREY LIQUIDS, SWEETLY AROMATIC
Percent Volatiles by Volume:70
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avo
id:YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
ALDEHYDES AND NITROGEN
Conditions to Avoid Polymerization:BLEND OF A AND B COMPONENTS WILL
SLOWLY POLYMERIZE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND
LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements

of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.