

FRANK MILLER & SONS, INC. -- SWEEPING COMPOUND -- 7930-00-132-5265

=====
Product Identification
=====

Product ID:SWEEPING COMPOUND

MSDS Date:03/24/1988

FSC:7930

NIIN:00-132-5265

MSDS Number: BHCXL

=== Responsible Party ===

Company Name:FRANK MILLER & SONS, INC.

Address:13831 SO. EMERALD AVENUE

Box:NA

City:CHICAGO

State:IL

ZIP:60627

Country:US

Info Phone Num:312-468-3500

Emergency Phone Num:312-46

8-3500

Preparer's Name:RICHARD L. KUDIA

CAGE:DO285

=== Contractor Identification ===

Company Name:FRANK MILLER & SONS, INC

Address:13831 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60627

Phone:312-468-3500

CAGE:DO285

Company Name:MILLER FRANK AND SONS INC

Address:13833 S EMERALD AVE

Box:City:CHICAGO

State:IL

ZIP:60627-1605

Country:US

CAGE:85702

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATE

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt

: 10-14%

Ingred Name:CELLULOSE (PAPER FIBER)

CAS:9004-34-6

RTECS #:FJ5691460

Fraction by Wt: 30-40%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3; 9192

Ingred Name:SAND

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 45-50%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Effects of Overexposure:EYE IRRITATION; SKIN IRRITATION OR DERMITITIS.

=====
===== First Aid Measures =====

First Ai

d:RINSE EYE WITH COPIOUS AMOUNTS OF WATER, SEEK PHYSICIAN IF NECESSARY. WASH SKIN WITH SOAP AND WATER.

=====
===== Fire Fighting Measures =====

Flash Point:NA

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:NORMAL AGENTS FOR EXTINGUISHING WOOD FIRES, WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:MATERIAL WILL SUPPORT COMBUSTION. MAY BE DRENCHED W/WATER TO REDUCE FIRE HAZARD.MATERIAL MAY SMOLDER AFTER IT IS INVOLVED IN A FIRE.

Unusual Fire/Explosion Hazard:SPREAD MATERIAL OUT AND BE SURE FIRE IS EXTINGUISHED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP MATERIAL AND RETURN TO CONTAINER OR DICARD.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE IN COOL, DRY PLACE. READ LABEL CAUTIONS AND DIRECTIONS BEFORE USE.

Other Precautions:KEEP OUT

OF THE REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USUALLY NOT REQUIRED

Ventilation:FRESH AIR

Protective Gloves:RECOMMENDED PERSONS SENSITIVE TO PETROLM

Eye Protection:GENERALLY NOT REQUIRED

Work Hygienic Practices:USE NORMAL GOOD HOUSEKEEPING PRACTICES.

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decom

p Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:5.20 #/GAL.

pH:NA

Evaporation Rate & Reference:NA

Solubility in Water:INSOLUABLE

Appearance and Odor:BROWN TO TAN GRANULAR MATERIAL, SLIGHT PETROLEUM
ODOR

Percent Volatiles by Volume:NA

Corrosion Rate:NA

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:IGNITION SOURCES

Hazardous Decomposition Products:CARBON DIOXIDE CARBON MON
OXIDE IF

BURNED

=====
===== Disposal Considerations =====

Waste Disposal Methods:MATERIAL MAY BE DUMPED, BUT FOLLOW LOCAL
POLLUTIONORDINANCES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any

person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.