

RELIABLE REMOVER & LACQUER CORP. -- NON FLAMMABLE PAINT REMOVER,FLOW ON
REMOVER -- 8010-00-597-8234

=====
Product Identification
=====

Product ID:NON FLAMMABLE PAINT REMOVER,FLOW ON REMOVER

MSDS Date:06/01/1989

FSC:8010

NIIN:00-597-8234

MSDS Number: BHDPQ

=== Responsible Party ===

Company Name:RELIABLE REMOVER & LACQUER CORP.

Address:62 WOOLSEY STREET

Box:NA

City:IRVINGTON

State:NJ

ZIP:07111

Coun

try:US

Info Phone Num:201-399-2121

Emergency Phone Num:201-399-2121

CAGE:OCA98

=== Contractor Identification ===

Company Name:RELIABLE REMOVER & LACQUER CORP.

Address:62 WOOLSEY STREET

Box:NA

City:IRVINGTON

State:NJ

ZIP:07111

Country:US

Phone:201-399-2121

CAGE:OCA98

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 PPM, A2; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:10

00 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:VOMITING, NAUSEA, DROWSINESS,
UNCONSCIOUSNESS, & EVEN DEATH IN EXTREME CASES.

Explanation of Carcinogenicity:HAS BEEN KNOWN TO CAUSE CANCER IN
L

LABORATORY ANIMALS

Effects of Overexposure:NAUSEA, DROWSINESS, VOMITING, UNCONSCIOUSNESS

Medical Cond Aggravated by Exposure:HEAT CONDITIONS AND ASTHMA

=====
===== First Aid Measures =====

First Aid:MOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING. IF BREATHING
HAS STOPPED, ADMINISTER ARTIFICIAL RESPIRATION. CALL
PHYSICIAN. IF EYE OR SKIN CONTACT FLUSH WITH WATER, NEVER
ADMINISTER ADRENALINE

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:NONE

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:CO2, FOAM, DRY CHEMICAL & WATER FOG

Fire Fighting Procedures:SELF CONTAINED BREATHING EQUIPMENT SHOULD BE
USED BY FIREMEN

Unusual Fire/Explosion Hazard:VAPORS CAN BE IGNITED BY HIGH ENERGY
IGNITION SOURCE. DECOMPOSES WITH FIRE OR HOT SURFACES TO ACIDIC
GASES AND OTHER TOXIC SUBSTANCES.

=====
===== Accidental Release Measures =====

Spill Release Procedur

es:STOP LEAK IF POSSIBLE. EVACUATE THE
AREA,VENTILATEAVOID BREATHING VAPORS OR COMING IN CONTACT WITH
LIQUID, CLEAN UP AREA (WEAR PROTECTIVE CLOTHING) CONTAIN SPILL.
REMOVE ALL SOURCE OF IGNITION OR HEAT.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID CONTACT W/SKIN & AVOID
VAPORS.PIPE VENT OUTDOORS.STORE IN COOL DRY AREA, PROVIDE
ADEQUATE VENTL.DONOT TRANSFER CONTENTS TO UNLABELED CONTNRS

Other Precautions:PROT
ECTIVE EQUIPMENT SUCH AS GLOVES & FACE SHIELD
SHALL BE WORN. IF PROPERLY USED A RESPIRATOR MAY OFFER
ADDITIONAL PROTECTION.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQUIRED WHEN USED WITH ADEQUATE
VENTILATION

Ventilation:LOCAL EXHAUST SUFFICIENT TO MAINTAIN BELOW TLV

Protective Gloves:NEOPRENE VITON, PVC COATED

Eye Protection:CHEMIICAL SAFETY GOGGLES/FULL FACE MASK

Other Protective Equipment:IMPERVIOUS APRON

Work Hygienic Pr

actices:OPEN CANS SLOWLY TO RELEASE VAPOR PRESSURE. DO
NOT SHAKE VIGOROUSLY.

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:104-120F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:20C J50

Vapor Density:2.9

Spec Gravity:1.3

Evaporation Rate & Reference:NA

Solubility in Water:MODERATE

Appearance and Odor:COLORLESS CLEAR LIQUID

=====
Stability and Reactivity Data
=====

Stability Indicator/

Materials to Avoid: YES

ALKALI METALS ALUMINUM, POTASSIUM, AND SODIUM OR PURE OXYGEN

Stability Condition to Avoid: CONTACT W/OPEN FLAMES, HOT SURFACES OR SPARKS FROM WELDING ARC.

Hazardous Decomposition Products: HYDROGEN CHLORIDE PHOSGENE AND OTHER HIGHLY TOXIC SUBSTANCE

===== Disposal Considerations =====

Waste Disposal Methods: CONSULT LOCAL POLLUTION CONTROL AGENCY

Disclaimer (provided with this information by the compiling agencies):

This informatio

n is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.