

SUNOX INCORPORATED -- NITROGEN -- 6830-00-598-9401

=====
Product Identification
=====

Product ID:NITROGEN
MSDS Date:04/08/1986
FSC:6830
NIIN:00-598-9401
MSDS Number: BHDQQ
=== Responsible Party ===
Company Name:SUNOX INCORPORATED
Address:4236 STATESVILLE ROAD
Box:33871
City:CHARLOTTE
State:NC
ZIP:28233
Country:US
Info Phone Num:(704) 596-6262
Emergency Phone Num:(803) 324-4180
CAGE:SUNOX
=== Contr
actor Identification ===
Company Name:SUNOX INCORPORATED
Address:4236 STATESVILLE ROAD
Box:33871
City:CHARLOTTE
State:NC
ZIP:28233
Country:US
Phone:704-596-6262
CAGE:SUNOX

=====
Composition/Information on Ingredients
=====

Ingred Name:NITROGEN
CAS:7727-37-9
RTECS #:QW9700000
ACGIH TLV:ASPHYXIAN; 9192

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:N

O

Effects of Overexposure: EXPOSURE MAY INCLUDE ANY, NONE, OR ALL OF THE FOLLOWING: LOSS OF BALANCE/DIZZINESS/TIGHTNESS IN THE FRONTAL AREA OF THE FOREHEAD; TINGLING OF TONGUE, FINGER TIPS, TOES, WEAKENED SPEECH, RAPID REDUCTION IN ABILITY TO PERFORM MOVEMENTS, REDUCED CONSCIOUSNESS OF SURROUNDINGS, LOST TACTILE SENSATIONS, OR HEIGHTENED MENTAL ACTIVITY.

=====
First Aid Measures
=====

First Aid: PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF

OVEREXPOSURE TO NITROGEN. RESCUE PERSONNEL SHOULD BE EQUIPPED W/SELF CONTAINED BREATHING APPARATUS. INHALATION: QUICK REMOVAL FROM THE CONTAMINATED AREA IS MOST IMPORTANT. UNCONSCIOUS PERSONS SHOULD BE MOVED TO AN UNCONTAMINATED AREA, GIVEN MOUTH TO MOUTH RESUSCITATION & SUPPLEMENTAL OXYGEN. IMMEDIATELY GET MEDICAL ASSISTANCE

=====
Fire Fighting Measures
=====

Flash Point: NA
Lower Limits: NA
Upper Limits: NA
Extinguishing Media: NON FLAMMABLE, INERT GAS
Fire Fighting Procedures: NA
Unusual Fire/Explosion Hazard: NA

=====
Accidental Release Measures
=====

Spill Release Procedures: EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE APPROPRIATE PROTECTIVE EQUIP. IF LEAK IS IN CONTAINER OR CONTAINER VALVE, CONTACT THE CLOSEST SUNOX LOCATION.

=====
Handling and Storage
=====

Handling and Storage Precautions: DO NOT DRAG, SLIDE, OR ROLL CYLINDERS. STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM HEAVY TRAFFIC. FULL & EMPTY CYLINDERS SHOULD BE SEGREGATED.
Other Precautions: COMPRESSED GAS CYLINDERS SHOULD NOT BE REFILLED EXCEPT BY QUALIFIED PRODUCERS OF COMPRESSED GASES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: POSITIVE PRESSURE AIR LINE W/MASK OR SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR EMERGENCY USE.

Ventilation: LOCAL EXHAUST TO PREVENT ACCUMULATION OF HIGH

C

CONCENTRATIONSSO AS TO REDUCE THE OXYGEN LEVEL IN THE AIR.

Protective Gloves:ANY MATERIAL

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:SAFETY SHOES

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:-320.445F

Vapor Pres:70F

Vapor Density:.07245

Appearance and Odor:COLORLESS,ODORLESS GAS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NO

NE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF WASTE OR UNUSED QUANTITIES. RETURN IN THE SHIPPING CONTAINER, PROPERLY LABELED. WITH VALVE OUTLET PLUGS OR CAPS SECURED & VALVE PROTECTION CAP IN PLACE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.