

NATINAL AEROSOL PRODUCTS COMPANY -- ENAMEL FLAT BLACK 37038 AEROSOL --  
8010-00-067-5437

=====  
===== Product Identification =====

Product ID:ENAMEL FLAT BLACK 37038 AEROSOL

MSDS Date:05/26/1988

FSC:8010

NIIN:00-067-5437

MSDS Number: BHFLL

=== Responsible Party ===

Company Name:NATINAL AEROSOL PRODUCTS COMPANY

Address:2103 E. 14TH STREET

City:LOS ANGELES

State:CA

ZIP:90021

Country:US

Emergency Phone Num:(

213) 627-2668

CAGE:JO968

=== Contractor Identification ===

Company Name:NATINAL AEROSOL PRODUCTS COMPANY

Address:2103 E. 14TH STREET

City:LOS ANGELES

State:CA

ZIP:90021

Country:US

CAGE:JO968

Company Name:NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

Address:2193 E 14TH STREET

Box:City:LOS ANGELES

State:CA

ZIP:90021-2843

Country:US

CAGE:59986

=====  
===== Composition/Information on Ingredients =====

Ingred Name:VM &P NAPHTHA

CAS:8030-30-6

RTECS #:QI9450000

Fraction by Wt: 40%

ingred Name:ACETONE (SARA III)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 35%  
OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTANE  
CAS:75-28-5  
Fraction by Wt: 25%

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Effects of Overexposure:INHL:HEADACHE, NAUSEA, & DIZZINESS.  
SKIN:PROLONGED OR REPEATED CONTACT MAY CAUSEIRRITATION.

=====  
===== First Aid Measures =====  
=====

First Aid:INHL:MOVE TO FRESH AIR. SKIN:FLUSH W/LARG AMOUNTS OF WATER.  
REMOVE CONTAMINATED CLOTHING. EYE: FLUSH W/WATER FOR 15 MINS.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:PMCC  
Flash Point:58F/14.44C  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM  
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE  
WORN BY FIREFIGHTERS  
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED  
TO COOL CONTAINERS  
EXPOSED TO FIRE.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:AVOID BREATHING VAPORS, EXTINGUISH IGNITION  
SOURCEIN IMMEDIATE AREA. AVOID CONTACT W/LIQUID

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions:DONOT STORE AT ELEVATED TEMPERATURE  
Other Precautions:CLOSE CONTAINERS AFTER USE.

=====  
===== Exposure Controls/Personal Protection =====  
=====

Respiratory Pr

Protection:ADEQUATE VENTILATION IS REQUIRED  
Ventilation:PROVIDE SUFFICIENT VENTILATION TO KEEP CONCENTRATION  
BELOW GIVEN TLV  
Protective Gloves:REQUIRED PROLONGED/REPEATED CONTACT  
Eye Protection:SOLVENT RESISTANT  
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING  
Work Hygienic Practices:NONE LISTED  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

HCC:V3  
Boiling Pt:B.P. Text:250-310  
Vapor Density:>AIR  
Spec Gravity:.999  
Evaporation  
Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:SLIGHT  
Appearance and Odor:BLACK,MOBILE LIQUID CONTAINING VOLATILE SOLVENTS  
Percent Volatiles by Volume:76.13

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
OXIDIZING MATERIALS, RUBBER SOFTENS  
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN CLOSED CO  
NTAINERS AWAY FROM  
IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this

information to their particular situation.