

PRODUCTS RESEARCH & CHEMICAL CORPORATION -- PRC RUBBER CALK 7000 SEALANT --  
8030-00-965-2397

===== Product Identification =====

Product ID:PRC RUBBER CALK 7000 SEALANT

MSDS Date:11/13/1986

FSC:8030

NIIN:00-965-2397

MSDS Number: BHFVC

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORPORATION

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

|

Info Phone Num:818-240-2060

Emergency Phone Num:818-240-2060

Preparer's Name:RBW

CAGE:8K647

=== Contractor Identification ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORPORATION

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:800-228-5635

CAGE:8K647

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/3

00STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:DILSODECYLPHTHALATE  
CAS:26761-40-0  
RTECS #:TI1270000

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Effects of Overexposure:EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE  
LOCAL IRRITATION. MAY CAUSE ALLERGIC SKIN RASH IN SENSITIZED  
INDIVIDUALS. INHALATION: MAY CAUSE IRRITATION TO NOSE AND THROAT.  
MAY CAUSE HEADACHE, DIZZINESS AND  
UNCONSCIOUSNESS.INGESTION: MAY  
CAUSE NAUSEA, VOMITING, LIVER AND KIDNEY DAMAGE.

=====  
===== First Aid Measures =====  
=====

First Aid:EYES: FLUSH WITH LUKEWARM WATER FOR 15 MINUTES. IF SYMPTOMS  
PERSIST, CONSULT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF  
SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE TO  
FRESH AIR. INGESTION: CONSULT A PHYSICIAN.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point  
t Method:PMCC  
Flash Point:88F/31.11C  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER  
Fire Fighting Procedures:USE AIR-SUPPLIED RESPIRATOR.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. SCOOP INTO  
CONTAIN-ERS. CLEAN UP RESIDUE WITH 1,1,1-TRICHLOROETHANE.

=====  
===== Exposure Controls/Personal Protection =====  
=====

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPOR BELOW PEL.  
Protective Gloves:SOLVENT R

ESISTANT GLOVES.  
Eye Protection:SAFETY GLASSES.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA  
Vapor Density:2.42(MEK)  
Spec Gravity:1.5  
Evaporation Rate & Reference:NA  
Solubility in Water:NEGLIGIBLE  
Percent Volatiles by Volume:3%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NK  
Hazardous Decomposition Products:OXIDES OF CARBON

=====  
=== Disposal Considerations =====

Waste Disposal Methods:EPA WASTE NO. D-001. DISPOSE OF SPILLAGE IN  
COM- PLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any perso  
n utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.