

CAAP COMPANY, INC. -- CURING AGENT,W/CAAPCOAT POLYURETHANE COATNG --  
8010-00-459-1756

===== Product Identification =====

Product ID:CURING AGENT,W/CAAPCOAT POLYURETHANE COATNG

MSDS Date:06/28/1988

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: BHFYS

=== Responsible Party ===

Company Name:CAAP COMPANY, INC.

Address:152 PEPES FARM RD

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Info Ph

one Num:203-468-0055

Emergency Phone Num:203-877-0375

Preparer's Name:RONALD D. ARENA

CAGE:LO402

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

Company Name:CAAP COMPANY, INC.

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Phone:203-468-0055

CAGE:LO402

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:1

08-10-1  
RTECS #:SA9275000  
OSHA PEL:100 PPM/75 STEL  
ACGIH TLV:50 PPM/75 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ALIPHATIC AMINE (TRADE SECRET)

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: CONTACT CORROSIVE TO EYES;  
SKIN IRRITANT, MAY CAUSE BURNS OR RASH. INHAL: UPPER  
RESPIRATORY IRRITATION,  
MAY BE TOXIC IN VERY HIGH DOSES.  
CHRONIC: WEIGHT LOSS; ANEMIA; LIVER,KIDN EY,SPLEEN POSSIBLE DAMAGE;  
POSSIBLE SENSITIZER. ROUTES OF INHAL. AND POSSIBLE SIGNIFICANT SKIN  
PENETRATION.  
Explanation of Carcinogenicity:THE PRODUCT GAVE NEGATIVE AMES SCREEN  
TEST RESULTS  
Effects of Overexposure:PUNGENT ODOR, UPPER RESPIRATORY IRRITATION; EYE  
IRRITATION, TEARING, BLURRING OF VISION, AND HEADACHE.  
Medical Cond Aggravated by Exposure:PREEXISTING LIVER DISEASE MAY BE  
AGGRAVATED

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH MUCH WATER & CALL PHYSICIAN.  
SKIN: WASH WITH SOAP AND WATER, REMOVE  
CONTAMINATED CLOTHING. INHAL: REMOVE TO FRESH  
AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY & CALL A PHYSICIAN.  
  
INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN

=====  
===== Fire Fighting Measures =====

Flash Point Method:TOC  
Flash Point:74F/23.33C  
Lower

Limits:0.9

Upper Limits:7.5

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:USE FULL PROTECTIVE GEAR, INCLUDING SCBA AND RUBBER OR OTHER CHEMICAL PROTECTIVESUIT FOR AMINE/AMMONIA TYPE CORROSIVE VAPORS.

Unusual Fire/Explosion Hazard:NONE. FLAMMABLE LIQUID AND CORROSIVE LIQUID WHEN WATER ADDED.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE SPILL & SOAK UP WITH ABSORBANT MATERIAL. USE PROTECTIVE GLOVES, MASK , GOGGLES, AND APRON. PLACE IN TIGHTLY SEALED CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IGNITION SOURCES AWAY. KEEP CLOSED WHEN NOT IN USE. KEEP AREA CLEAN. STORE IN COOL, DRY PLACE. Other Precautions:AVOID CONTACT WITH SKIN, EYES, AND CLOTHING. DO NOT BREATH VAPOR OR MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED SPECIAL CARBON CANNISTER, SCBA, OR SUPPLIED AIR FOR EMERGENCY USE.

Ventilation:LOCAL EXHAUST PREFERRED; SPECIAL SPRAY BOOTH IS RECOMMENDED FOR SPRAY.

Protective Gloves:NEOPRENE OR POLYETHYLENE

Eye Protection:SAFETY GOGGLES SPLASH PROOF

Other Protective Equipment:RUBBER OR POLYETHYLENE APRON. EMERGENCY EYE WASH AND SHOWER

Work Hygienic Practices:WASH W/SOAP & WATER AFTER HANDLING. KEEP AREA NEAT AND CLEAN

Supplemental Safety and Health

KEY1:F4. KIT CONSISTS OF EIGHT PARTS. PART ONE HAS PNI A, PART TWO HAS

PNI B, PART THREE HAS PNI C ... THROUGH PNI H, SAME NSN.

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:231-266F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:3

Vapor Density:3.7

Spec Gravity:0.83

Evaporation Rate & Reference: