

DYKEM COMPANY -- DX-100 DYKEM STEEL BLUE -- 6850-01-276-5396

===== Product Identification =====

Product ID:DX-100 DYKEM STEEL BLUE

MSDS Date:10/05/1989

FSC:6850

NIIN:01-276-5396

MSDS Number: BHGCF

=== Responsible Party ===

Company Name:DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST LOUIS

State:MO

ZIP:63114

Info Phone Num:314-423-0100

Emergency Phone Num:314-423-0100

CAGE:EO153

=== Contractor Ide

ntification ===

Company Name:DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST. LOUIS

State:MO

ZIP:63114-5905

Country:US

Phone:314-423-0100

CAGE:EO153

Company Name:ITW DYKEM/ DYMON

Address:805 E OLD 56 HWY

Box:City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:800-443-9536

CAGE:98148

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 30-40%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;91

92
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 50-60%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 3-6%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL VIOLET
CAS:8004-87-3
RTECS #:GC8425000
Fraction by Wt: 6-12%

Ingred Name:CELLULOSE NITRATE (PROPORTIONAL 70/30 WITH ISOPRO
PANOL)
CAS:9004-70-0
RTECS #:QW0970000
Fraction by Wt: 2.1-4.2%

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 0.9-1.8%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS IRRITATING TO BODY TISSUES.
PROLONGED/REPEATED SKIN

CONTACT MAY CAUSE DERMATITIS. INHALATION
MAY PRODUCE CENTRAL NERVOUS SYSTEM EFFECTS. NO INFORMATION WAS
READILY AVAILABLE ON CHRONIC EFFECTS.

Effects of Overexposure:EYE:IRRITATION,BURNING. SKIN:DRYING,DERMATITIS
WITH PROLONGED/REPEATED CONTACT. INHALED:RESPIRATORY
IRRITATION,DIZZINESS,HEADACHE,NAUSEA. INGESTED:G/I
IRRITATION,NAUSEA.

Medical Cond Aggravated by Exposure:NONE REPORTED

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:REMOVE CONTAMINATED
CLOTHING. WASH AREA WITH SOAP AND WATER. LAUNDRY CLOTHING BEFORE
REUSE. INHALED:REMOVE FROM EXPOSURE. GIVE ARTIFICIAL RESPIRATION OR
OXYGEN IF NEEDED. INGESTED:DO NOT INDUCE VOMITING. GIVE WATER OR
MILK. (NOTHING BY MOUTH IF UNCONSCIOUS) GET IMMEDIATE MEDICAL CARE.
IF SYMPTOMS PERSIST OR ARE SEVERE,GET MEDICAL CARE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:57F/14C
Lower
Limits:1.4
Upper Limits:11.2
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL,FOAM,WATER FOG
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. WATER
MAY BE USED TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND FLASHBACK
ALONG VAPOR TRAIL MAY OCCUR

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP,WITH PAPER,CLOTH. STORE IN CLOSED
CONTAINER. USE APPROPRIATE PRECAUTIONS TO PROTECT PERSONNEL AND
PREVENT IGNITION.
Neutralizing Agent:NONE- USE ALCOHOL AS SOLVENT FOR CLEANING.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL VENTILATED
AREA. KEEP AWAY FROM HEAT,SPARKS,OTHER IGNITION SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE EXPECTED TO BE NECESSARY. USE NIOSH/MSHA
RESPIRATOR IF SYMPTOMS OCCUR OR PEL/TLV ARE EXCEEDED.

Ventilation:NORMAL ROOM VENTILATION LOCAL EXHAUST MAY BE REQUIRED UNDER SOME CONDITIONS.

Protective Gloves:NONE SHOULD BE NEEDED

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:AS NECESSARY TO PREVENT PROLONGED/REPEATED CONTACT.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT.

Supplemental Safety and Health

MFR DATES MSDS ON DAY MAILED,NOT DAY REVISED.

===== Physical/Chemical Properties =====

HCC:F2

Boili

ng Pt:=71.1C, 160.F

Vapor Pres:36 MM

Vapor Density:>1

Spec Gravity:0.86

Evaporation Rate & Reference:>1 BUAC

Solubility in Water:APPRECIABLE

Appearance and Odor:INTENSE BLUE COLOR,SWEET SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT,IGNITION SOURCES

Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE.

===== Disposal Considerati
ons =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL,REGULATIONS.
MFR SUGGESTS INCINERATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compet

ent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.