View NSN Online: https://aerobasegroup.kr/nsn/6850-00-826-0981

Product ID:FLAW-FINDER AG-RH CLEANER (PRE 3/90) MSDS Date:01/03/1989 FSC:6850 NIIN:00-826-0981 Kit Part:Y **MSDS Number: BHHPP** === Responsible Party === Company Name: AMERICAN GAS AND CHEMICAL COMPANY., LTD. Address:220 PEGASUS AVENUE City:NORTHVALE State:NJ ZIP:07647-1904 Country:US Info Phone Num:201-767-7300 Emergency Phone Num:201-767-7300 Preparer's Name: GEORGE KOSEL, CHIEF CHEM CAGE:03530 === Contractor Identification === Company Name: AMERICAN GAS AND CHEMICAL COMPANY, LTD Address:220 PEGASUS AVENUE, City:NORTHVALE State:NJ ZIP:07647-1904 Country:US Phone:201-767-7300 CAGE:03530

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by W t: 96.0% OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

Ingred Name:CARBON DIOXIDE CAS:124-38-9 RTECS #:FF6400000 OSHA PEL:5000 PPM ACGIH TLV:5000PPM/30000STEL;93

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATO RY TRACT;HEADACHE,DIZZINESS,ANESTHETIC

EFFECTS, CNS DEPRESSION; CHRONIC: DEFATTING, DERMATITIS; HEALTH STUDIES HAVE SHOWN THAT MANY HALOGENATED HYDROCARBONS POSE PO TENTIAL HUMAN HEALTH RISKS WHICH MAY VARY FROM PERSON TO PERSON. Explanation of Carcinogenicity: MFRG STATED THAT 1,1,1-TRICHLOROETHANE HAS BEEN SUBJECTED TO A CARCINOGENESIS BIOASSAY BY NCI AND FOUND NOT A CARCINOGEN

Effects of Overexposure:INHALATION:HIGH VAPOR CONC CAUSES IRRITATION,HEADACHE,DIZZINESS AND CNS

DEPRESSION;SKIN:PROLONGED/REPEATED CONTACT TENDS TO REMOVE SKIN OIL POSSIBLY LEADING TO IRRITATION AND DERMATITIS;EYES:LIQ CONTA CT MAY CAUSE IRRITATION;INGESTION:PRODUCT HAS LOW ORDER OF ACUTE ORAL TOXICITY.MINUTE QTY INSPIRATED IN LUNGS IS FATAL. Medical Cond Aggravated by Exposure:NONE REPORTED BY THE MANUFACTURER. HOWEVER,PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid:INHALATION:REMOVE TO FRESH AIR:SE EK MEDICAL HELP.IF BREATHING IS IRREGULAR OR HAS STOPPED,START RESUSCINATION;ADMINISTER OXYGEN IF AVAILABLE; SKIN AND EYES:FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINU TES.SEEK MEDICAL HELP IF IRRITATION PERSISTS;INGESTION:DO NOT INDUCE VOMITING.IMMEDIATELY CALL A PHYSICIAN.

Flash Point:NONE Lower Limits:7.5 Upper Limits:15.0 Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,WATER SPRAY OR FOG. Fire Fig hting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREA.COOL EXPOSED CONTAINERS WITH WATER SPRAY.AVOID BREATHING VAPOR OR FUMES.

Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST/EXPLODE IN HEAT OF FIRE.

Spill Release Procedures: USE PROPER PERSONAL PROTECTION: REMOVE ALL IGNITION SOURCES: RECOVER FREE LIQUID; USE SUITABLE INERT ABSORBENT MATERIAL SUCH AS SAND, SAWDUST, ETC.. TO ABSORB SPILLED

LIQUID.VENTILATE CONFINED SPACES.KEEP MATERIAL OUT OF SEWERS AND WATER COURSES.

Handling and Storage Precautions:STORE IN A COOL DRY PLACE BELOW 120F.DO NOT PUNCTURE OR INCINERATE AEROSOL CANS.DO NOT STORE OR HANDLE NEAR HEAT,SPARKS OR OXIDANTS.

Other Precautions: DO NOT

PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION: THEY MAY E

XPLODE AND CAUSE INJURY OR DEATH.DO NOT ATTEMT TO CLEAN SINCE RESIDUE IS DIFFICULT TO REMOVE.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: USE SUPPLIED-AIR RESPIRATOR PROTECTION IN CONFINED AREA, IF NEEDED.

Ventilation:PROVIDE >60FPM HOOD FACE VELOCITY.LOCAL EXHAUST TO MAINTAIN PEL/TLV (USE EXPLOSION PROOF EQUIPMENT.)

Protective Gloves: USE CHEMICAL RESISTANT OTHER THAN RUBBER Eye Protection: FACE SHIELD/SPLASH PROOF GOGGLES.

Other Protec

tive Equipment:USE CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING,IF NEEDED,TO AVOID CONTAMINATING REGULAR CLOTHING.EYE-WASH FAC

Supplemental Safety and Health

NSN MANAGED BY GSA IS A 3 PART KIT OF TYPE II,METHOD C;PER GSA ID,KIT CONSISTS OF 9-7 OZ AEROSOL CANS (3 CANS EACH OF PENETRANT,DEVELOPER,AND CLEANER);PER MIL-I-25135,REV E AND QPL-25135-14/15,THIS RE MOVER,AG-RH,IS QUALIFIED WITH PENETRANTAG-1-VS, & D-4 DEVELOPER,AG-DH;SEE PNI-A&B FOR PENETRANT & DEVELO PER;KEY1:V2.

HCC:V2 Vapor Pres:100MMHG@20 Vapor Density:4.55 Spec Gravity:1.32 (BULK) Evaporation Rate & amp; Reference:1.33 (WATER=1) (BULK) Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS LIQUID;SWEET ODOR Percent Volatiles by Volume:>99%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENT,STRONG CAUSTICS,REACTIVE METALS LIKE ALU MINUM. Stability Condition to Avoid:EXTREME HEAT Hazardous Decomposition Products:HYDROGEN CHLORIDE,SMALL AMOUNT OF PHOSGENE AND CHLORINE.

Waste Disposal Methods:DISPOSE OF RECOVERED MATERIAL AT AN APPROVED DISPOSAL SITE OR FACILITY.CAN BE RECLAIMED AND RECYCLED.ASSURE CONFORMITY WITH ALL APPLICABLE LOCAL,STATE AND FEDERAL DISPOSAL REGULATIONS.DO NOT INCINERAT E AEROSOL CANS EMPTY OR FILLED.

Disclaimer (provi

ded with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.