View NSN Online: https://aerobasegroup.kr/nsn/6810-00-687-8056

VAN WATERS AND ROGERS INC -- METHANOL -- 6810-00-687-8056

Product ID:METHANOL MSDS Date:04/12/1988 FSC:6810 NIIN:00-687-8056 **MSDS Number: BHKCQ** === Responsible Party === Company Name: VAN WATERS AND ROGERS INC Address:2600 CAMPUS DRIVE Box:5932 **City:SAN MATEO** State:CA ZIP:94403-2522 Country:US Info Phone Num:LOCAL VAN WATERS & ROGERS BRANCH **Emergency Phone Num:800** -424-9300 (CHEMTREC) CAGE:0AN91 === Contractor Identification === Company Name: CHEMICAL COMMODITIES AGENCY, INC. Address:27447 PACIFIC STREET Box:City:HIGHLAND State:CA ZIP:92346-2640 Country:US Phone:909-864-2310 CAGE:60777 Company Name: VAN WATERS AND ROGERS Address:2256 JUNCTION AVE City:SAN JOSE State:CA ZIP:95131 Country:US Phone:408-435-8700/800-424-9300(CHEMTREC) CAGE:0AN91

Ingred Name: METHYL ALCOHOL (METHANOL) (SARA I

II) CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: >99% OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 5628 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHALE: MILD INTOXICATION. TOXIC EFFECTS ARE EXERTED ON THE CNS, ESPECIAL LY THE OPTIC NERVE. EYE: LIQUID AND MISTS WILL IRRITATE AND MAY BURN THE EYES. SKIN: IRRITATION, DERMATITIS, AND SYSTEMI C CHANGES. INGEST: 100-150 ML. MAY BE FATAL! LESSER AMOUNTS- BLINDNESS, DIZZINESS, HEADACHES, OR NAUSEA. Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:SEE HEALTH HAZARDS. CHRONIC HAZARDS: PROLONGED OR REPEATED EXPOSURE MAY RESULT IN CNS DAMAGE, BLINDNESS, DAMA GE TO

PANCREAS, OR DEATH.

Medical Cond Aggravated by Exposure:NONE REPORTED.

First Aid:INHALATION: REMOVE SUBJECT TO FRESH AIR. MAINTAIN BREATHING AND GET DR. EYE: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMIN ATED CLOTHING. SEE DR. IF IRRITAION PERSISTS. INGESTION: IMMEDIATELY INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

=

Flash Point Method:TCC Flash Point:52.0F,11.1C Lower Limits:6 Upper Limits:36.5 Extinguishing Media:USE CARBON DIOXIDE, ALCOHOL FOAM, DRY CHEMICAL, OR WATER SPRAY. DO NOT USE A DIRECT WATER STREAM. Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:EXTIN

GUISH ALL NEARBY SOURCES OF IGNITION. THIS PRODUCT MAY BURN WITH A FLAME WHICH IS INVISIBLE IN DAYLIGHT. MIXTURES WITH WATER AND 21% METHANOL ARE FLAMMABLE

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. EXTINGUISH ALL IGNITION SOURCES. ABSORB WITH NON-COMBUSTIBLE SORBENT MATERIAL, AND PLACE IN APPROVED CONTAINERS. KEEP OUT OF SEWERS, STORM DRAINS AND SURFACE WATER. Neutralizing Agent:NONE APPLICABLE FO R THIS MATERIAL

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE, HEAT AND IGNITION SOURCES. KEEP CONTAINERS CLOSED.

Other Precautions:CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, WILL RETAIN PRODUCT RESIDUE AND VAPORS. ALWAYS OBEY HAZARD WARNINGS AND HANDLE EMPTY CONTAINERS AS IF THEY WERE FULL.

===== Exposure Controls/Personal Protection ====

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS REQUIRED. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA IS NOT VENTED.

Protective Gloves:RUBBER

Eye Protection: CHEMICAL SAFETY GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. OTHER EQUIPMENT AS

REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

HCC:F2 Boiling Pt:B.P. Text:148F,64C Melt/Freeze Pt:M.P/F.P Text:-144F,-98C Vapor Pres:96 Vapor Density:1.1 Spec Gravity:0.79 Evaporation Rate & amp; Reference:>2 (BUTYL ACETATE=1) Solubility in Water:100 App Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, ALUMINUM, ZINC, ANY METAL THAT DISPLACES HYDROGEN, CERTAIN PLASTICS, RUBBERS, ACIDS, ALKALIS.
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, FORMALDEHYDE AND UNIDENTIFIED ORGANIC COMPOUNDS IN BLACK SMOKE.

====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. NOTE: EMPTY CONTAINERS CAN HAVE RESIDUES, GASES AND MISTS AND ARE SUBJECT TO PROPER WASTE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoeve r,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.