

SEYMOUR OF SYCAMORE INC -- GP-5163-4087 OLIVE DRAB -- 8010-00-848-9272

=====
Product Identification
=====

Product ID:GP-5163-4087 OLIVE DRAB

MSDS Date:11/09/1992

FSC:8010

NIIN:00-848-9272

MSDS Number: BHLTH

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE INC

Address:917 CROSBY AVE

City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Info Phone Num:815-892-9101

Emergency Phone Num:815-891-9

101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

=====
Composition/Information on Ingredients
=====

Ingred Name:TITANIUM DIOXIDE, TIO2

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 2.09%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:DICHLOROMETHANE (METHYLENE CHLORIDE) (SUSPECTED HUMAN
CARCINOGEN

BY ACGIH, NTP)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 30%
OSHA PEL:500 PPM
ACGIH TLV:174 MG/CUM (A2)
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 2.62%
Other REC Limits:1900 MG/CUM
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 9.12%
Other REC Limits:100 PPM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM, SKIN
EPA Rpt Qty:10
00 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 1.14%
Other REC Limits:100 PPM
OSHA PEL:435 MG/CUM
ACGIH TLV:434 MG/CUM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:EPOXYPROPANE, PROPYLENE OXIDE
CAS:75-56-9
RTECS #:TZ2975000
Fraction by Wt: 0.15%
Other REC Limits:20 PPM
OSHA PEL:100 PPM
ACGIH TLV:20 PPM; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 11.01%
Other REC

Limits:375 MG/CUM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHANOL (METHYL ALCOHOL), COLUMBIAN SPIRITS
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 0.12%
Other REC Limits:200 PPM
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL
CARBINOL
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 0.27%
Other REC Limits:400 PPM
OSHA PEL:400 PPM
ACGIH TLV:400 PPM

Ingred Name:V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: 0.10%
Other REC Limits:STEL 400 PPM
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:2-BUTOXYETHANOL (ETHYLENEGLYCOL MONOBUTYL ETHER), BUTYL
CELLOSOLVE, BUTYL GLYCOL, GLYCOL ETHER EB
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 0.91%
Other REC Limits:25 PPM (SKIN)
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX227

5000
Fraction by Wt: 18%
Other REC Limits:1800 MG/CUM
OSHA PEL:1000 PPM
ACGIH TLV:SIMPLE ASPHYXIAN

Ingred Name:ISOBUTANE, 2-METHYLPROPANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 12%
Other REC Limits:1000 PPM
OSHA PEL:1800 MG/CUM
ACGIH TLV:1000 PPM

Ingred Name:LEAD DRIER, LEAD (DRY FILM)
Fraction by Wt: 8.76%

Ingred Name:WEIGHT PER GALLON IN POUNDS: 7.221 LB/GAL
RTECS #:9999999WG

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:
n:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:RESPIRATORY SYSTEM AND EYE IRRITANT.
SKIN: DEFATTING & DERMATITIS. CHRONIC: INHALATION:
CARBOXYHEMOGLOBINEMIA, CNS EFFECTS INCLUDING DEATH, LIVER & KIDNEY
EFFECTS. INGESTION: ASPIRATION HAZARD.
Explanation of Carcinogenicity:SEE INGREDIENTS
Effects of Overexposure:INHALATION: IRRITATION, HEADACHE, DIZZINESS,
NAUSEA, DROWSINESS, FATIGUE, NARCOSIS, POSSIBLE UNCONSCIOUSNESS
&
ASPHYXIATION. EYES: IRRITATION. SKIN: DEFATTING, LEADING TO
IRRITATION.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, BEGIN
ARTIFICIAL RESPIRATION. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST
15 MINS. SKIN: WASH W/SOAP & WATER. INGESTION: OBTAIN MEDICAL
ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:-10F(P)

ROPELLANT)

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT BURSTING. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES & SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. WIPE UP W/INERT MATERIALS & PLACE IN APPROPRIATE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE >120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING. USE ONLY AS DIRECTED. USE W/ADEQUATE VENTILATION.

Other Precautions:INTENTIONAL MISUSE BY DEILBERATELY CONCENTRATING VAPORS & INHALING CONTENTS CAN BE HARMFUL OR FATAL. AVOID BREATHING OF VAPORS & SPRAY MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A SELF CONTAINED BREATHING APPARATUS REQUIRED FOR CONCENTRATION ABOVE TLV.

Ventilation:ADEQUATE VENTILATION, SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS.

Protective Gloves:OPTIONAL

Eye Protection:ONLY IF SPRAY MIST MIGHT GET INTO EYES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume

:84/WT

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING MATERIALS

Stability Condition to Avoid: TEMPS >120F, SPARKS, PILOT LIGHTS, OPEN
FLAME

Hazardous Decomposition Products: CO₂, CO

===== Disposal Considerations =====

Waste Disposal Methods: DON'T INCINERATE AEROSOL, DISPOSE OF IN
ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. DON'T PLACE
AEROSOL CANS IN HOME COMPACT
OR. DON'T PUNCTURE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to thei

r

particular situation.