

BAKER SEALANTS -- PAINT PHOSPHORESCENT GREEN X-649 -- 8010-00-181-7165

===== Product Identification =====

Product ID:PAINT PHOSPHORESCENT GREEN X-649

MSDS Date:11/29/1989

FSC:8010

NIIN:00-181-7165

MSDS Number: BHMGR

=== Responsible Party ===

Company Name:BAKER SEALANTS

Address:234 SUYDAM AVENUE

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-333-6986

Emergency Phone Num:201-333-6  
986

Preparer's Name:MARIO NAVARRO

CAGE:EO611

=== Contractor Identification ===

Company Name:BAKER SEALANTS

CAGE:EO611

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 7.0%

OSHA PEL:100 PPM

===== Hazards Identi

fication =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION MAY CAUSE LOSS OF BALANCE  
AND COORDINATION, UNCONSCIOUSNESS, COMA, RESPIRATORY FAILURE AND  
DEATH.  
Explanation of Carcinogenicity:NONE KNOWN.  
Effects of Overexposure:EYES: MAY CAUSE MINIMAL IRRITATION. SKIN:  
MODERATE IRRITANT. REMOVES NATURAL OIL& FATS FROM SKIN WITH  
PROLONGED/REPEATED CONTACT.  
INHALE: MAY IRRITATE NOSE, THROAT,  
CENTRAL NERVOUS SYSTEM. ALSO INGESTION: HARMFUL IF VOMITING  
OCCURS,PULMONARY ASPIRATION HAZARD AND/OR FATAL.  
Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER 15 MINS. OBTAIN MEDICAL ASSISTANCE.  
SKIN: WASH WITH SOAP & WATER UNTIL NO ODOR REMAINS, IF  
REDNESS/SWELLING DEVELOPS, GET MEDICAL ATTENTION. INHALE: REMOVE  
TO FRESH AIR, GIVE ART  
IFICIAL RESPIRATION. GET MEDICALATTENTION.  
INGESTION: DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:120F/48.9C  
Autoignition Temp:Autoignition Temp Text:\*\*\*  
Lower Limits:0.9  
Upper Limits:7  
Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL.  
Fire Fighting Procedures:WEAR SCBA. VAPORS ARE >AIR & MAY TRAVEL A  
CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION & FLASH BACK. KEEP  
AWAY FROM HEAT,SPARKS,PILOT LIGHTS,OPEN FLAME  
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR AND MAY TRAVEL A  
CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.  
KEEP AWAY FROM STATIC ELEC.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. WEAR  
APPROVED BREATHING APPARATUS. DIKE AREA AND USE INERT  
MATERIAL TO ABSORB LIQUID.  
Neutralizing Agent:NONE KNOWN.

=====

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS AND STORAGE CONTAINERS  
CLOSED WHENNOT IN USE. DO NOT STORE NEAR, HEAT, SPARKS, FLAMEOR  
STRONG OXIDANTS.

Other Precautions:NONE KNOWN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILATION.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:SAFETY GLASSES AND/OR  
GOGGLES.

Other Protective Equipment:IMPERVIOUS APRON, EYE WASH FACILITY AND/OR  
EMERGENCY SHOWER.

Work Hygienic Practices:NONE KNOWN.

Supplemental Safety and Health  
NONE KNOWN.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:240F/116C

Melt/Freeze Pt:M.P/F.P Text:OF/-18C

Vapor Pres:15 MMHG

Vapor Density:3.8

Spec Gravity:1.34

pH:7.0

Viscosity:500-3500 CPS

Evaporation Rate & Reference:9.20

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN LI

QUID/ACRYLIC ODOR

Percent Volatiles by Volume:30

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

THERMAL DECOMPOSITION MAY OCCUR.

Stability Condition to Avoid:AVOID STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:AS PER FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this infor

mation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.