

INDUSTRIAL FLOOR FINISHES -- KAR WAX -- 7930-00-281-3267

=====
Product Identification
=====

Product ID:KAR WAX
MSDS Date:12/01/1985
FSC:7930
NIIN:00-281-3267
MSDS Number: BHMJL
=== Responsible Party ===
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRINGS RD
City:BEDFORD
State:MA
ZIP:01730
Country:US
Info Phone Num:1-617-667-5161
Emergency Phone Num:1-800-424-9300
Preparer's Name:T. PITROLF
FY
CAGE:INDUS
=== Contractor Identification ===
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRINGS RD
City:BEDFORD
State:MA
ZIP:01730
Country:US
Phone:1-617-667-5161
CAGE:INDUS

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 69%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestio

n: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Effects of Overexposure: EYE IRRITATION, DRYING SKIN, MAY CAUSE
HEADACHE, DIZZINESS, AND NAUSEA

=====
First Aid Measures
=====

First Aid: EYE: FLUSH WITH WATER. SKIN: WASH WITH MILD SOAP AND WATER,
APPLY SKIN CREAM AND INHALATION: REMOVE TO FRESH AIR AND CALL
PHYSICIAN

=====
Fire Fighting Measures
=====

Flash Point Method: TCC
Flash Point: 104F/40.00C
Lower Limits: 6.9
Upper Limits: 0.7
Extinguishing Media: WATER SPRAY, CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures: NONE
Unusual Fire/Explosion Hazard: NONE

=====
Accidental Release Measures
=====

Spill Release Procedures: SCRAPE UP MATERIAL FROM SURFACE AND COLLECT IN
METAL CONTAINER

=====
Handling and Storage
=====

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND OPEN
FLAME. USE ADEQUATE VENTILATION

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS ABOVE TLV
LIMITS
Ventilation: LOCAL EXHAUST
Protective Gloves: YES
Eye Protection: YES
Other Protective Equipment: EYE BATH
Work Hygienic Practices: GENERAL
Supplemental Safety and Health
NK

=====
Physical/Chemical Properties
=====

Boiling Pt: B.P. Text: 311F
Vapor Pres: 2
Vapor Density: 4.7
Spec Gravity: 0.7
Evaporation Rate & Reference: 0.12
Solubilit

y in Water:NEGLIGIBLE
Appearance and Odor:LT. BLUE, WAXY ODOR
Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NK
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME
Hazardous Decomposition Products:THERMAL DECOMPOSTION MAY YIELD CARBON
MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS, DISPOSE OF IN
ACCORDAN
CE WITH LOCAL, STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of
this information to their
particular situation.