

CHEMRAY COATINGS, CORP. -- PRIMER FOR WOOD AND METAL -- 8010-00-664-6302

=====
Product Identification
=====

Product ID:PRIMER FOR WOOD AND METAL
MSDS Date:11/01/1989
FSC:8010
NIIN:00-664-6302
MSDS Number: BHMSY
=== Responsible Party ===
Company Name:CHEMRAY COATINGS, CORP.
Address:209 N. MICHIGAN AVE.
Box:NA
City:KENILWORTH
State:NJ
ZIP:07033
Country:US

Info Phone Num:201-245-1111

Emergency Phone

Num:201-245-1111

CAGE:OBRN9

==== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

Company Name:CHEMRAY COATINGS CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:800-924-9300

CAGE:OBRN9

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 3

9%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Health Hazards Acute and Chronic:OVEREXPOSURE - NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION
Effects of Overexposure:OVEREXPOSURE - NAUSEA, HEADACHE, DIZZINESS
CAUSED BY OVER INHALATION
Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER 15 MIN. UNTIL IRRI SUBSIDES, IF IRRI
PERSISTS CALL PHYSICIAN.SKIN: REMOVE CONTAMINATED CLOTHING & WASH
THROUGHLY WITH SOAP & WATER. INHAL: IF OVERCOME BY VAPORS,
REMOVE TO FRESH AIR, CALL PHYSICIAN.INGST: DO NOT INDUCE VOMITING
CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:103 F/40 C
Lower Limits:0.9
Upper Limits:7
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY C
HEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS AND
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT
SPARKS& OPEN FLAMES. ADD ABSORBENT (SAND, EARTH, ETC.) VENT AREA.
IF LG SP

ILL KEEP PRODUCT FROM ENTERING SEWERS/WATERCOURSES BY
DIKING. ADVISE AUTHORITIES IF PRODUCT ENTERS WATER SYSTEM

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP
IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT &
EXTREME TEMPERATURES HOT OR COLD

Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION & INGESTION OF
MISTS, SPRAY OR VAPORS. AVOIDBREATHING SANDING OR BLASTING DUST.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATOR IN CONFINED AREA.

Ventilation:LOCAL EXHAUST-FACE VELOCITY 60FPM SPECIAL-USE ONLY WITH
ADE-QUATE VENTILATION. MECH-USE EXPLOSION PROOF EQUIPMENT

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING

Supplemental Safety and Health

NK

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:308 F

Decomp Temp:Decomp Text:600 F

Vapor Pres:< 10 @ 77F

Vapor Density:4.8

Spec Gravity:1.234

pH:NA

Evaporation Rate & Reference:0.09

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WHITE LIQUID WITH KEROSENE ODOR

Percent Volatiles by Volume:62

Corrosion Rate:NA

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CAN REACT W/OXIDIZING MATERIAL WHEN H

EATED TO DECOMPOSTION.

Stability Condition to Avoid:HIGH TEMPERATURE

Hazardous Decomposition Products:CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REG
DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR
FACILITY. DISPOSE IN COMFORMITY WITH STATEAND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated fo

r use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.