

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS GRN 14050 ID742404 -- 8010-00-753-4550
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS GRN 14050 ID742404

MSDS Date:03/23/1988

FSC:8010

NIIN:00-753-4550

MSDS Number: BHMVB

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. ELLISON

C

AGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:Y

ES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONG/REPEATED OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE MAY BE HARMFUL OR FATAL. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION.

Explanation of Carcinogenicity:MANUFACTURER CONCLUDES THAT THERE IS NO SIGNIFICANT HAZARD FOR MAN.

Effects

of Overexposure:INGEST: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING. INHAL: NOSE/THROAT IRRITATION, HEADACHES, DIZZINESS, NAUSEA, AND CONFUSION. EYE: IRRITATION SKIN: IRRITATION AND DEFLATTING OF SKIN

===== First Aid Measures =====

First Aid:INGEST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY INHAL: REMOVE TO FRESH AIR IMMEDIATELY, GIVE ARTIFICIAL RESPIRATION IF NECESSARY, KEEP WARM & QUIET, GET MEDICAL ATTENTION IMMEDIATELY; EYE: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING EYELIDS FOR AT LEAST 15 MIN. GET MEDICAL ATTENTION; SKIN: REMOVE CONTAMINATED CLOTHES. WASH AFFECTED AREA WITH SOAP & WATER. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:> 102 F/38.89 C
Extinguishing Media:NFPA CL B FIRE EXTINGUISHING (CARBON DIOXIDE, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR EXTINGUISHING FLAMMABLE LIQUID FIRES. POLYMER FOAM PREFERRED
Fire Fighting Procedures:SELF CONTAINING BREATH APPARATUS. WATER MAY BE INEFFECTIVE, USED TO COOL TO PREVENT PRESSURE BUILD-UP/AUTO-IGNITION/EXPLOSION FROM HEAT. IF WATER USED, FOG NOZZLES PREFERRED
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, & FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL WITH INERT MATERIAL. USE NON SPARKING

materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid: EXCESSIVE HEAT & SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDE WHEN HEATED BY WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATION. DO NOT INCIN

ERATE CLOSED CONTAINERS INCINERATE ONLY

IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document s

ould seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.