

ELDORADO CHEMICAL COMPANY, INC. -- PR-3500, PAINT REMOVER -- 8010-00-926-1488

=====
Product Identification
=====

Product ID:PR-3500, PAINT REMOVER

MSDS Date:07/27/1988

FSC:8010

NIIN:00-926-1488

MSDS Number: BHMXY

=== Responsible Party ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265

Country:US

Info Phone Num:512-653-9323

Eme

rgency Phone Num:800-531-1088

Preparer's Name:PAT E. SMITH

CAGE:55208

=== Contractor Identification ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Phone:800-531-1088/ 210-653-2060

CAGE:55208

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 50%

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 PPM, A2; 9192

EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PHENOL
CAS:108-95-2
RTECS #:SJ3325000
Fraction by Wt: 17%
OSHA PEL:5 PPM
ACGIH TLV:5 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM CHROMATE
CAS:7775-11-3
Fraction by Wt: 0.8%
OSHA PEL:NONE
ACGIH TLV:.5 PPM
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INAHL: ACUTE, ABSORBED IN LUNGS &
CHRONIC, NONE. SKIN: ACUTE, CORROSIVE & CHRONIC, SLIGHT. SKIN:
ACUTE, SLIGHT & CHRONIC, NONE. EYES: ACUTE, CORROSIVE &
CHRONICSLIGHT.
Effects of Overexposure:INHAL: NARCOSIS, DIZZINESS, NAUSEA, REDUCES
OXYGEN IN BLOOD. SKIN: CORROSIVE, DERMATITIS MAY OCCUR. SKIN:
CONTACT IS PAINFUL, SKIN ABSORPTION WOULD BE UNLIKELY.NO CHRONIC
HAZARD. AND EYE: BURNS IMMEDI ATELY AND NO CHRONIC HAZARD EXPECTED

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MIN. CONSULT PHYSICIAN. SKIN:
FLUSH WITH WATER FOR15 MIN., WASH WITH SOAP AND WATER AND INHAL:
REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:1200 F
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:NONE
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS REQUIRED
Unusual Fire

/Explosion Hazard:TOXIC CHLORIDE FUMES MAY BE GENERATED BY
CONTACT WITH FLAME

===== Accidental Release Measures =====

Spill Release Procedures:RINSE WITH WATER

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA REQUIRED IF LIMITS EXCEEDED

Ventilation:100 FT/MIN

Protective Gloves:POLYETHYLENE

Eye Protection:FACE SHIELD/GOGGLES

Other Protective Equipment:RUBBER APRON & BOOTS

Supplemental Safety and Health

NK

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:120 F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:380 MM

Vapor Density:2.9 AIR

Spec Gravity:1.15

pH:9.2

Evaporation Rate & Reference:(WATER=1) 1

Solubility in Water:PARTIALLY SOLUBLE

Appearance and Odor:THICK YELLOW LIQUID PHENOL ODOR

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

STRONG ALKALIS, STRONG OXIDIZERS

Hazardous Decomposition Products:HEAT WILL PRO

DUCE DICHLOROMETHANE

FUMES

===== Disposal Considerations =====

Waste Disposal Methods:USEPA HAZARDOUS WASTE NO.'S UO80, 8188, DOOZ

CONSULT FEDERAL, STATE AND LOCAL REGULATORY AGENCIES FOR PROPER

DISPOSAL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants th

is information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.