

PRATT & LAMBERT, INC. -- LACQUER ACRYLIC WHITE 17875, ID794716 -- 8010-00-935-6608
===== Product Identification =====

Product ID:LACQUER ACRYLIC WHITE 17875, ID794716

MSDS Date:10/14/1988

FSC:8010

NIIN:00-935-6608

MSDS Number: BHMYN

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

E

mergency Phone Num:316-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt

Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:VOC. ORGANIC CMPD 5.0 LB/GAL LESS WATER & NPRS* 600 G/L
LESS WATER VOC. 16.2 LB/GAL SOLIDS 1944 G/L SOLIDS CALCU
RTECS #:9999999VO

Ingred Name:VOC 4.96 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY
REACTIVE MATERIALS 595 G/L LESS WATER CALCULATED
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 16.20 LB/GAL SOLIDS 1944 G/L

SOLIDS CALCULATED
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ASPIRATION OF MATL INTO LUNG MAY CAUSE
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. ACUTE CENTRAL NERVOUS
SYSTEM DEPRESSION; LIQ. MATL MAY BE ABSORBED THROUGH THE SKIN IN
HARMFUL AMNTS.; TOLUENE MAY CAUSE LI
VER DAMAGE. OVEREXPOSURE TO
SOLVENTSCAN CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. MISUSE
CAN BE HARMFUL/FATAL.
Effects of Overexposure:EYE: MAY CAUSE IRRITATION
SKIN: MAY CAUSE IRRITATION OR
DEFATTING OF SKIN INHAL:
NOSE/THROAT IRRIT. HEADACHES, DIZ ZINESS, NAUSEA, AND
CONFUSIONINGST: GASTROINTESTINAL IRRITATION, NAUSEA, AND VOMITING.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/LG AMNTS OF WTR FO
R 15 MINS.,LIFTING EYELIDS,GET
MEDICAL ATTENTION.SKIN: WASH AFFECTED AREA W/SOAP & WTR,REMOVE
CONTAMINATED CLOTHES,GET MED. ATTN.INHAL: REMOVE TO FRESH AIR,GIVE
ARTIFICI AL RESPIRATION, KEEP WARM/QUIET, GET MEDICAL ATTENTION
IMMEDIATELY
INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN OR HOSPITAL
IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:24F/-4.44C
Extinguishing Media:USE NFPA CLASS BE FIRE EXTINGUISHERS. POL
YMER FOAM
IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:SHOULD WEAR SCBA. WTR MAYBE INEFFECTIVE, BUT
MAY BE USED TO COOL EXPSD CONTNRS TO PREVENT PRESS. BUILDUP WHEN
EXPOSED TO EXTRM HEAT.FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE
TO DECOMPOSTION PRODUCTS MAY CAUSE A HEALTH HAZARD. WARNING!!!
FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE A

LL SOURCES OF IGNITION. DIKE &

CONTAIN SPILL W/INERT MATL. USE ONLY NON SPARKING TOOLS. PLACE
ABSORBENT DIKING MATL IN COVERED METAL CONTAINER FOR DISPOSAL.
PREVENT CONTAMINATION OF SEWER STREAMS,& GROUNDWATER W/SPILLED MATL
OR ABSORBENT

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORE ABOVE 95F. STORE LG QTYS IN
COMPLIANCE WITH OSHA 29CFR1910.106. CLOSE CONTAINER AFTER EACH
USE. NEVER USE PRESSURE TO EMPTY CONTAINERS.

Other Precautions: DO NOT TAKE INTERNALLY. EMPTY CONTAINERS MUST NOT BE
WASHED AND REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE
GROUNDED/BONDED TO RECEIVING CONTAINERS. DO NOT WELD, BRAZE OR CUT
ON EMPTY CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: RESTRICTED AREAS USE A NIOSH APPROVED CHEMICAL
CARTRIDGE RESPIRATOR. FOR SPRAYING USE A MECHANICAL
PREFILTER. CONFINED AREAS
USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation: GENERAL DILUTION AND LOCAL EXHAUST

Protective Gloves: IMPERMEABLE GLOVES

Eye Protection: SAFETY GLASSES

Other Protective Equipment: NONE LIKELY NEEDED

Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: 175-314F

Vapor Density: > AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 69

=====
===== Stability and Reactivity Data =====

===

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDING W/HEATED BY WELDING/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/FEDERAL, STATE, & LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE ONLY IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.