

INDUSTRIAL FLOOR FINISHES -- KAR WAX -- 7930-00-985-6750

===== Product Identification =====

Product ID:KAR WAX

MSDS Date:12/01/1985

FSC:7930

NIIN:00-985-6750

MSDS Number: BHMZZ

=== Responsible Party ===

Company Name:INDUSTRIAL FLOOR FINISHES

Address:605 SPRING STREET

City:BEDFORD

State:MA

ZIP:01730

Country:US

Info Phone Num:1-617-5161 OR POISON CENTER

Emergency Phone Num:1-617-5161 OR POISON CENTE

R

Preparer's Name:T. PITROLFFY

CAGE:INDUS

=== Contractor Identification ===

Company Name:FEDERAL SPECIFICATIONS, PROMULGATED BY GSA

Box:City:WASHINGTON

State:DC

Country:US

CAGE:81348

Company Name:INDUSTRIAL FLOOR FINISHES

Address:605 SPRINGS RD

City:BEDFORD

State:MA

ZIP:01730

Country:US

Phone:1-617-667-5161

CAGE:INDUS

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 69%

OSHA PEL:500 PPM

ACGIH TLV:1

00 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYE IRRITATION, DRYING SKIN, MAY CAUSE
HEADACHE, DIZZINESS, NAUSEA.
Effects of Overexposure:EYE IRRITATION, DRYING SKIN, MAY CAUSE
HEADACHE, DIZZINESS, NAUSEA.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER. SKIN CONTACT: WASH WITH MILD
SOAP AND WATE
R, APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH
AIR AND CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:104 F/ 40.00 C
Lower Limits:0.7
Upper Limits:6.9
Extinguishing Media:WATER SPRAY, CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP MATERIAL FROM SURFACE & COLLECT IN
ME
TALCONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN
FLAME. USE ADE-QUATE VENTILATION. AVOID PROLONGED CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS ABOVE TLV
LIMITS
Ventilation:LOCAL EXHAUST
Protective Gloves:RECOMMENDED
Eye Protection:RECOMMENDED
Other Protective Equipment:EYE BATH
Supplemental Safe

ty and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:311

Vapor Pres:2

Vapor Density:4.7

Spec Gravity:0.78

Evaporation Rate & Reference:0.12 (TOLENE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER SPRAY, CO2, FOAM, DRY CHEMICAL

Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME

Hazard

ous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS, DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly o

r implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.