

NILES CHEMICAL PAINT COMPANY -- N 1207A EARTH YELLOW CAMO TYPE IV -- 8010-01-131-0612
===== Product Identification =====

Product ID:N 1207A EARTH YELLOW CAMO TYPE IV
MSDS Date:10/11/1989
FSC:8010
NIIN:01-131-0612
Kit Part:Y
MSDS Number: BHNDR
=== Responsible Party ===
Company Name:NILES CHEMICAL PAINT COMPANY
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Info Phone Num:6
16-683-3377 (INFORMATION)
Emergency Phone Num:219-236-5856 (24 HOURS)
Preparer's Name:MIKE LICHATOWICH
CAGE:02388

=== Contractor Identification ===
Company Name:NILES CHEMICAL PAINT
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Phone:616-683-3377/219-236-5856
CAGE:02388

===== Composition/Information on Ingredients =====

Ingred Name:PM ACETATE
(VAPOR PRESSURE 3.7 MM @ 20C)
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 17%
OSHA PEL:N

E
ACGIH TLV:NE

Ingred Name:POLYESTER RESIN
Fraction by Wt: 16%

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 9%
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 7%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISO
MERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 3%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CHROMIUM (III) OXIDE
CAS:1308-38-9
RTECS #:GB6475000
Fraction by Wt: 1%
OSHA PEL:0.5 MG/M3 (CR)
ACGIH TLV:0.5 MG/M3 (CR); 8990

Ingred Name:VOC. ORGANIC CMPD 4.33 LB/GAL
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Repo

Health Hazards Acute and Chronic: HISTOLOGIC FIBROSIS OF LUNGS, INCOHERENCE, CORNEAL VACUOLIZATION, ANOREXIA. TARGET ORGANS: CNS, LUNGS, EYES, SKIN, RESPIRATORY SYSTEM, GI TRACT, BLOOD, LIVER, AND KIDNEYS. IF INHAL. CAN CAUSE NASAL/RESPIRATORY IRRITATION, CNS DEPRESS, DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, CONFUSION, POSS. UNCONSCIOUSNESS, OR ASPHYXIATION

Effects of Overexposure: EYE: SEVERE IRRITATION, LACRIMATION, REDNESS, BLUR

RED VISION SKIN: REDNESS, IRRITATION, DEFATTING OF SKIN LEADING TO DERMATITIS. INHL: NAUSEA, HEADACHE, VERTIGO INGEST: GASTROINTESTINAL IRRITATION, ABDOMINAL PAIN, NAUSEA, VOMITING, DIARRHEA

Medical Cond Aggravated by Exposure: NONE

===== First Aid Measures =====

First Aid: EYE: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. LIFTING EYELIDS, GET MEDICAL ATTENTION SKIN: IMMEDIATELY FLUSH WITH WATER, IMMEDIATELY REMOVE CONTAMINATED CLOTHING, GET MEDICAL ATTENTION IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION IF NEEDED, GET MEDICAL ATTENTION INGESTION: DRINK 1-2 GLASSES OF WATER. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 20F/-6C

Lower Limits: 1.0

Upper Limits: 10

Extinguishing Media: DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures: WEAR SCBA WITH FULL FACEPIECE OPERATED WITH POSTVAPOR PRESSURE MODE & FULL PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP/IGNITION OR EXPLOSION

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINER MAY EXPLODE WITH EXPOSURE TO EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL ON GROUND TO AN IGNITION SOURCE. ISOLATE FROM HEAT, ELECTRICITY, FLAME.

===== Accidental Release Measures =====

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. ABSORB WITH INERT MATERIAL SUCH AS CLAY, SOIL, OR COMMERCIALY AVAILABLE ABSORBENT INTO RECOVERY OR RECLAIMED LIQUID & ABSORBENT INTO RECOVERY OR

SALVAGE DRUMS FOR
DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMP AREAS OR
NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN
USEAVOID ROUGH HANDLING.CONTNRS MAYBE HAZARD. W/EMPTY
Other Precautions:DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. CONTACT
LENSES SHOULD NOT BE WORN WHEN WORKING WITH THIS MATERIAL. IF MATL
PENETRATES THE CLOTHING, IMMEDIATELY REMOVE THE CONTAMINATED
CLOTHING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR
DURING & AFTER APPLICATION UNLESS AIR MONITORYING DEMONSTRATES
VAPOR/MIST LVLS ARE BELOW APPLICABLE LIMITS.
Ventilation:SUFFICIENT VENTL IN VOLUME & PATTERN SHOULD BE PROVIDED TO
KKEEP THE AIR CONCENTRATION BELOW CURRENT TLV LIMIT.
Protective Gloves:CHEMICAL RESISTANT GLOVES
Eye Protection:CHEM GOGGLES/SAFETY GLASSES/FACESHIELDS
Other Pro
tective Equipment:CLOTHING AS NEEDED TO PREVENT SKIN CONTACT.
Work Hygienic Practices:WASH HANDS BEFORE EATING,SMOKING,OR USING
RESTROOMS. WASH CLOTHING AND SHOES BEFORE REUSE.
Supplemental Safety and Health
EMPLOYEES SHOULD WASH PROMPTYL WHEN SKIN BECOMES CONTAMINATED. REMOVE
ANY CLOTH-ING THAT BECOMES WET (TO AVOID FLAMMABILITY HAZARD).

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:***
Vapor Density:> AIR
Viscosity:70-85 KU
Evaporation Ra
te & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:LIQUID, ODOR OF SOLVENTS
Percent Volatiles by Volume:57.72

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS
Stability Condition to Avoid:HIGH TEMPERATURES, SHOCK FROM DROPPING
Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE/DIOXIDE
Conditions to Avoid Polymerization:*** BOIL PT: 175-302F/79-150

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.