

BAKER SEALANTS & COATINGS COMPANY -- CORROSION-PREVENTIVE COMPOUND --
8030-00-546-8637

===== Product Identification =====

Product ID:CORROSION-PREVENTIVE COMPOUND

MSDS Date:11/16/1989

FSC:8030

NIIN:00-546-8637

MSDS Number: BHQKR

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATINGS COMPANY

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:1-2

01-333-6986 8:00 AM TO 4:00 PM

Emergency Phone Num:1-800-424-9300 CHEMTREC 24 HRS.

Preparer's Name:MARIO NAVARRO

CAGE:FO833

=== Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

===== Composition/Informa

tion on Ingredients =====

Ingred Name:SOLVENT 140
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 19%
ACGIH TLV:25 PPM

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III)
CAS:76-13-1
RTECS #:KJ4000000
Fraction by Wt: 72%
OSHA PEL:1000PPM/1250STEL
ACGIH TLV:1000PPM/1250STEL9192
Ozone Depleting Chemical:1

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:LIGHT HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, POSSIBLE NARCOSIS, POSSIBLE CARDIAC ARRHYTHMIAS, AT HIGH CONCENTRATION LEVEL.
Effects of Overexposure:LIGHT HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, POSSIBLE NARCOSIS, POSSIBLE CARDIAC ARRHYTHMIAS, IF OVER EXPOSURE IS EXPERIENCED.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER SKIN: FLUSH WITH WATER.
INHALATION: REMOVE TO FRESH AIR. CALL A PHYSICIAN, DO NOT GIVE EPINEPHRIN.

===== Fire Fighting Measures =====

Flash Point:NR
Extinguishing Media:STRAIGHT WATER STREAM WOULD SPREAD OIL FIRES.
Unusual Fire/Explosion Hazard:VAPOR ACCUMULATION WOULD FLASH AND/OR EXPLODE IF IGNITED.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA ESPECIALLY LOW PLACES WHERE HEAVY VAPORS MIGHT COLLECT; REMOVE OPEN FLAMES

===== Handling and Storage =====

age =====

Handling and Storage Precautions:STORE CONTAINERS IN A CLEAN, DRY AREA,
DO NOT HEAT ABOVE 125F.

Other Precautions:USE PROPER SAFETY EQUIPMENT WHEN NECESSARY, DO NOT
HEAT PRODUCT ABOVE 125F.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AIR MASK IN HIGH CONCENTRATIONS.

Ventilation:LOCAL EXHAUST: WHEN LARGE AMOUNTS ARE RELEASED, ESPECIALLY
IN LOW PLACES.

Protective Gloves:WHEN HANDLING LIQUID.

Eye Prot

ection:WHEN HANLING LIQUID.

Supplemental Safety and Health

VAPORIZATION OF EXCESSIVE AMOUNT OF THIS PRODUCT CAN DELETE OR REPLACE
OXYGEN NECESSARY FOR BREATHING. IN CONFINED/ENCLOSED SPACES OR
AREA WITH LITE VENTILA- TION THIS MAY BE HAZARDOUS TO HEALTH. EX
POSURE TO HIGH CONCENTRATIONS OF THISPRODUCT.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:117 F-139 F

Vapor Pres:334MMHG@68

Vapor Density:5.4

Spec Gravity:1.22-1.27

Evaporat

ion Rate & Reference:0.3

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK AMBER ORGANIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALI OR ALKALINE EARTH METALS POWDERED.

Stability Condition to Avoid:AVOID OPEN FLAMES OR HIGH TEMPERATURES

Hazardous Decomposition Products:HYDROCHLORIC AND HYDROFLUORIC ACIDS

===== Disposal Considerations =====

Waste Disposal Methods:RECLAIM BY

DISTILLATION

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.