View NSN Online: https://aerobasegroup.com/nsn/8030-00-881-3933

THE FLAMEMASTER CORPORATION -- CS 3300, PART B -- 8030-00-881-3933

Product ID:CS 3300, PART B MSDS Date:07/25/1989

FSC:8030

NIIN:00-881-3933

Kit Part:Y

MSDS Number: BHQMZ === Responsible Party ===

Company Name: THE FLAMEMASTER CORPORATION

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA ZIP:91352 Country:US

Info Phone Num:1-818-982-1650 Emergency Phone Num:1-80 0-424-9300 CHEM TREC

CAGE:6N186

=== Contractor Identification ===

Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949 Country:US

Phone:818-982-1650

CAGE:14439

Company Name: THE FLAMEMASTER CORPORATION

CAGE:6N186

======= Composition/Information on Ingredients ========

Ingred Name: LEAD PEROIXIDE (CATALYST) *

CAS:1309-60-0

RTECS #:OG0700000 OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3

Ingred Name:LEAD OXIDE *

CAS:1317-36-8

RTECS #:OG1750000 OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: WEAKNESS AND STUPOR. CHRONIC: KIDNEY DAMAGE, ANEMIA, AND REPRODUCTIVE DEFECTS. Effects of Overexposure: HEADACHE, MUSCLE AND JOINT PAIN, ALSO NEUROMUSCULAR DYSFUNCTION. Medical Cond Aggravated by Ex posure: ANEMIA, KIDNEY DISEASE AND PREGNANCY. First Aid:INGESTION: INDUCE VOMITING, CONSULT A PHYSICIAN AT ONCE. EYE CONTACT: FLUSH WITH LARGE AMOUNT OF WATER AND CONTACT PHYSICIAN. Flash Point Method:TCC Flash Point:> 200 F/> 93 C Extinguishing Media: FOAM, DRY CHEMICAL, CO2, WATER. Fire Fighting Procedures: USE A SELF-CONTAINED BREATHIN **G APPARATUS WITH** FULL FACE-PIECE, IN CONFINED AREAS Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT WITH OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS. ========= Accidental Release Measures ============ Spill Release Procedures: SCOOP UP AND TRANSFER TO A SAFETY CONTAINER. ============ Handling and Storage =========================== Handling and Storage Precautions: STORE IN A COOL AND DRY AREA. KEEP CONTAINERS CLOSED. Other Precautions:WA

====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF DUST IS FORMED USE NIOSH APPROVED RESPIRATOR. Ventilation:LOCAL EXHAUST; AIR HOOD. MECHANICAL (GENERAL); FAN. Protective Gloves:RUBBER GLOVES. Eye Protection:SAFETY GLASSES. Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT. Work Hygienic Practices:TRAIN PERSONNEL IN THE SAFE HANDLING OF THIS PRODUCT.
Supplemental Safety and Health * TH
E EXPOSURE LIMITS ARE BASED ON DUST PARTICLES. IN THIS PRODUCT THE LEAD DIOXIDE/OXIDE PARTICLES ARE WETTED OUT THEREFORE AIRBORNE PARTICLES WILL NOT RESULT FROM NORMAL USE.
========== Physical/Chemical Properties ============
Boiling Pt:B.P. Text:340 C Melt/Freeze Pt:M.P/F.P Text:SEE BELOW Vapor Pres:NEGLIGIBLE Vapor Density:NA Spec Gravity:3.00 Evaporation Rate & amp; Reference:NEGLIGIBLE Solubility in Water:NEGLIGIBLE Appearance and Odor:BROWN PASTE WITH AN OILY O DOR. (MELTING POINT: LIQUID AT ROOM TEMP.)
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES OXIDIZABLE MATERIALS. Stability Condition to Avoid:HIGH HEAT. Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGANICS.
========= Disposal Considerations ==============
Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT WITH BASE AND DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL REGULAT

SH HANDS BEFORE EATING, DRINKING OR SMOKING.

IONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.