

PRATT & LAMBERT, INC. -- ADDUCT FOR FLAT COLOR COMP B PART 2 OF 2 -- 8010-00-756-2411  
===== Product Identification =====

Product ID:ADDUCT FOR FLAT COLOR COMP B PART 2 OF 2

MSDS Date:01/16/1989

FSC:8010

NIIN:00-756-2411

Kit Part:Y

MSDS Number: BHQTZ

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:316-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 10%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:4

00 PPM/500STEL;9192

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER

CAS:107-98-2

RTECS #:UB7700000

Fraction by Wt: 65%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

Ingred Name:VOC. ORGANIC CMPD 5.7 LB/GAL LESS WATER & NPRS\* 684 G/L

LESS WATER VOC. 24.4 LB/GAL SOLIDS 2928 G/L SOLIDS CALCU

RTECS #:9999999VO

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO

OSHA:NO

Health Hazards Acute and Chronic:ASPIR. OF MATL INTO LUNG MAY CAUSE

CHEM. PNEUMONITIS CAN BE FATAL. HIGH CONCENTRATION MAY CAUSE ACUTE  
CENTRAL NERVOUS SYSTEM DEPRESSION. OVEREXPOSURE TO SOLVENTCAN CAUSE  
PERMANENT BRAIN & NERVOUS SYST EM DAMAGE. INTENTIONAL MISUSE CAN  
BE HARMFUL OR FATAL.

Effects of Overexposure:EYE: MAY CAUSE IRRITATION.

SKIN: MAY CAUSE DEFATTING &  
IRRITATION OF SKIN. INHAL:  
ANESTHETIC,NOSE & THROAT IRRIT.,H  
EADACHE,DIZZINE

SS,CONFUSION,NAUSEA,UNCONSCIOUSNESS,& ASPHYXIATION;

INGST: GASTROINTESTINAL IRRIT.,NAUSEA,& VOMITING

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH W/LG AMNTS OF WTR FOR 15 MINS,LIFTING EYELIDS,GET  
MEDICAL ATTENTION SKIN: WASH AFFECTED AREA W/SOAP & WTR,REMOVE  
CONTAMINATED CLOTHES,GET MED. ATTN.INHAL: REMOVE TO FRESH AIR  
IMMEDIATELY,G IVE ARTIFCL RESPIRATION IF NEEDED, KEEP WARM &  
QUIET,GET MEDICAL ATTENTION IMMEDIATELY

INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY!!

=====  
===== Fire Fighting Measures =====

Flash Point:53F/11.67C

Extinguishing Media:USE NFPA CLASS BE FIRE EXTINGUISHERS. POLYMER FOAM  
IS PERFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SCBA. WTR MAY BE INEFFECTIVE,MAY BE USED  
TO COOL EXPOSED CONTAINERS TO PRE-VENT PRESS. BUILDUP & POSS. IGN.  
W/EXPSD TO EXTRM HEAT.W/WTR FOG NOZZLES PREFERD

Unusual Fire/Explosion Hazard:EMERG COND OVE

REXPOSURE DECOMP PROD CAUSE

HEALTH HAZARD. SYMP MAY NOT BE IMMED. APPARENT. OBTAIN MEDICAL ATTENTION. WARNING!! FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL W/INERT MATERIAL. USE NON SPARKING TOOL ONLYPLACE ABSORBENT DIKING MATL IN COVERED METAL CONTAINER FOR DISPOSAL. PREVENT CONTAMINATION OF SEWERS STREAMS,GROUNDWATER W/SPILLED MATL OR USED ABSORB

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LG QTYS IN COM-PLIANCE W/OSHA 29CFR1910.106. CLOSE CONTAINERS AFTER EACH USE. NEVER USE PRESSURE TO EMPTY.

Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST. EMPTY CONTAINERS MUST NOT BE WASHED & REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED & BONDED TO THE RECEIVING CONTAINER. DO NOT WELD,BRA ZE OR CUT ON EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED AREAS US NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING USE AMECHANICAL FILTER RESPIRATOR. CONFINED AREAS USE A NIOSH APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:LOCAL EXHAUST VENTILATION OR GENERAL DILUTION

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING OR DRINKING

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:179-248F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:76

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION

Hazardous Decomposition Produc

ts:BURNING, INCLUDE W/HEATED BY WELD OR  
CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.  
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL. DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.