

DAVLIN PAINT CO -- ZINC DUST PORTION ENAMEL -- 8010-00-290-6645

===== Product Identification =====

Product ID:ZINC DUST PORTION ENAMEL

MSDS Date:01/01/1987

FSC:8010

NIIN:00-290-6645

Kit Part:Y

MSDS Number: BHRGR

=== Responsible Party ===

Company Name:DAVLIN PAINT CO

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:415-848-2863

Emergency Phone Num:415-889-7098

Preparer's Name:PAT

RICIA SHAW

CAGE:91007

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO

Address:1401 E 14TH

Box:City:OAKLAND

State:CA

ZIP:94606-4401

Country:US

CAGE:91007

===== Composition/Information on Ingredients =====

Ingred Name:ZINC DUST

CAS:7440-66-6

Fraction by Wt: 95%

ACGIH TLV:15 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

Fraction by Wt: 4.2%

OSHA PEL:15MG/M3 TDUST/5 FUME

ACGIH TLV:10MG/M3 TDUST; 9293

Ingred

Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: .12%  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:CADMIUM (SARA III)  
CAS:7440-43-9  
RTECS #:EU9800000  
Fraction by Wt: .04%  
OSHA PEL:SEE 1910.1027  
ACGIH TLV:0.01 MG/M3 DUST;9394  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Effects of Overexposure:;  
EXCESSIVE INHALATION OF FRESHLY FORMED FUME  
MAY PRODUCE SYMPTOMS KNOWN AS "FUME FEVER" OR "ZINC SHAKES".  
INDIVIDUAL FEELS HEADACHY AND FEVERISH.

===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:NA  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:CO2, DRY CHEMICAL, DRY SAND  
Fire Fighting Procedures:COVER TO EXCLUDE AIR AND MOISTURE;  
DONOT USE  
WATER SINCE UNDER CERTAIN CONDITIONHYDROGEN MAY BE FORMED.  
Unusual Fire/Explosion Hazard:WATER DRIPPING SLOWLY INTO DRUM OF DUST  
STORED IN UNVENTED AREA. SPARKS IN CLSD CONVEYOR SYSTEM HANDLING  
ZINC DUST MAY CAUSE EXPLOSIONS.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP AND SHOVEL UP OR VACUUM CLEAN IF  
REQUIRED. RETURN TO CONTAINER.

===== Handling and Storage =====

Handling and

Storage Precautions:STORE IN DRY CONTAINER AND KEEP AWAY FROM MOISTUREACIDS & STRONG ALKALI HYDROXIDE.

Other Precautions:HAVE HANDLERS OF UNPACKED DUST WASH HANDS PRIOR TO MEALS. DO NOT ALLOW SMOKING IN AREAS WHERE DUST IS HANDLED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATORS IF LOCAL EXHAUST FAILS OR CONCENTRATOR EXCEEDS THE TLV.

Ventilation:LOCAL EXHAUST RECOMMENDED

Protective Gloves:RECOMMENDED

Eye

Protection:RECOMMENDED

Other Protective Equipment:NA

Supplemental Safety and Health

NK

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:1663F

Vapor Pres:.004 @327F

Vapor Density:NA

Spec Gravity:7.1

Evaporation Rate & Reference:NA

Solubility in Water:REACTS W/WATER

Appearance and Odor:DARK GREY POWDER; NO ODOR

Percent Volatiles by Volume:NA

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YE

S

NK

Stability Condition to Avoid:MOISTURE, WATER, HIGH HUMIDITY WHEN IN CLOSED SYSTEMS.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN DRY, CLOSED AND MARKED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be ac

curate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.