

WHIP MIX CORPORATION -- LUBRITEX 12 DIE LUBRICANT -- 6520-01-265-0102

===== Product Identification =====

Product ID:LUBRITEX 12 DIE LUBRICANT

MSDS Date:08/25/1988

FSC:6520

NIIN:01-265-0102

MSDS Number: BHTXP

=== Responsible Party ===

Company Name:WHIP MIX CORPORATION

Address:361 FARMINGTON AVENUE

City:LOUISVILLE

State:KY

ZIP:40217

Info Phone Num:(502) 637-1451

Emergency Phone Num:(502) 637-1451

CA

GE:FO337

=== Contractor Identification ===

Company Name:WHIP MIX CORPORATION

Address:361 FARMINGTON AVENUE

City:LOUISVILLE

State:KY

ZIP:40217

Phone:(502) 637-1451

CAGE:FO337

Company Name:WHIP-MIX CORP

Address:361 FARMINGTON AVE

Box:City:LOUISVILLE

State:KY

ZIP:40217

Country:US

Phone:502-637-1451

CAGE:12164

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Other REC Limits:1900 MG/CUM

OSHA PEL:1000 PPM

ACGIH TL

V:1000 PPM; 9192

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Other REC Limits:400 PPM

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Other REC Limits:200 PPM

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:Y

ES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: INEBRIATION, HEADACHE,
NAUSEA & VOMITING, DROWSINESS. SKIN: MAY CAUSE DRYNESS &
IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: INEBRIATION, HEADACHE, NAUSEA,
VOMITING & DROWSINESS. SKIN: DRYNESS & IRRITATION.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES.

SKIN: WASH W/SOAP &

WATER. INHALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION
IF BREATHING HAS STOPPED. CALL PHYSICIAN. INGESTION: INDUCE
VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:61F

Lower Limits:3.3%

Upper Limits:19.0%

Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM, WATER FOG

Fire Fighting Procedures:KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAME.
KEEP CONTAINER CLOSED.

===== Accid

ental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. SMALL SPILLS SHOULD BE FLUSHED WITH WATER.

===== Handling and Storage =====

Handling and Storage Precautions:WARNING: FLAMMABLE KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAME. KEEP CONTAINER CLOSED. USE W/ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Phy
sical/Chemical Properties =====

Boiling Pt:B.P. Text:172F

Vapor Pres:42

Spec Gravity:0.8

Solubility in Water:COMPLETE

Appearance and Odor:DARK VIOLET COLOR, CHARACTERISTIC ALCOHOL ODOR.

Percent Volatiles by Volume:75%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME

Hazardous Decomposition Products:CO, CO2

===== Disposal Considerati
ons =====

Waste Disposal Methods:NO SPECIAL TREATMENT REQUIRED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume r

responsibility for the suitability of this information to their particular situation.