

CHEMRAY COATING CORP -- PAINT RUB-BASE INT CONCRET/MASONR GRAY16187 --
8010-00-297-2102

=====
===== Product Identification =====

Product ID:PAINT RUB-BASE INT CONCRET/MASONR GRAY16187

MSDS Date:09/11/1989

FSC:8010

NIIN:00-297-2102

MSDS Number: BHVRZ

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245

-1111

Emergency Phone Num:201-245-1111

Preparer's Name:FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====
===== Composition/Information on Ingredients =====

Ingred Name:PM ACETATE

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 47%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:SUPER HIFLASH NAPHTHA

CAS:64742-95-6

Fraction by Wt:

10%
OSHA PEL:200 PPM
ACGIH TLV:100 PPM

Ingred Name:VOC=5.44 LBS/GAL OR 653 GRAMS/LITER MAX VOC AFTER
THINNING=5.67 LBS/GAL OR 681 GRAMS/LITER
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION.
Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED
BY OVER INHALATION.
Medical
Cond Aggravated by Exposure:NONE GENERALLY KNOWN.

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT;
REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER.
INHALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL
PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====
Fire Fighting
Measures
=====

Flash Point Method:SCC
Flash Point:81 F/ 27 C
Autoignition Temp:Autoignition Temp Text:960 F
Lower Limits:1.8
Upper Limits:11.0
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL.
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENT AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP PRODUCT FROM ENTERING SEWERS/WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF DOES ENTER.

===== Handling and Storage =====

Handling and Storage Precautions: STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT & EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions: AVOID EYE, SKIN CONTACT, INHALATION OR INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS.

Ventilation: LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY W/ADEQUATE

VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT.

Protective Gloves: CHEMICAL RESISTANT.

Eye Protection: SPLASH GOGGLES OR FACE SHIELDS.

Other Protective Equipment: USE CHEMICAL RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt: B.P. Text: 311F, 155C

Melt/Freeze Pt: M.P/F.P Text: 0 F (-17.8C)

Decomp Temp: Decomp Text: 600 F (316C)

Vapor Pres: