

CHEMRAY COATING CORP -- VARNISH, SPAR, PHENOLIC RESIN -- 8010-00-597-7856

=====
Product Identification
=====

Product ID:VARNISH, SPAR, PHENOLIC RESIN

MSDS Date:10/27/1989

FSC:8010

NIIN:00-597-7856

MSDS Number: BHVTC

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:20

1-245-1111

Preparer's Name:FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 41%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:VOC=3.07 LBS/GAL OR 368 GRAMS/LITER

RTECS #:9999999VO

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION.

Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED
BY OVER INHALATION. HIGH VAPOR CONCENTRATIONS (>1000 PPM), ARE
IRRITATING TO EYES & RESPIRATORY TRACT, ARE ANESTHETIC & MAY HAVE
OTHER CENTRAL NERVOUS S YSTEM EFFECTS.

Medical Cond Aggravated by Ex
posure:NONE GENERALLY KNOWN.

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER.
INHALATIO N: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL A
PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC

Flash Point:103 F/40 C

Autoignition Temp:Autoignition Temp Text:473 F

Lower Limits:0.9

Upper Limits:7

Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL.

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR
FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT,
SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL.
VENTILATE AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP FROM
ENTERING SEWERS & WATERCOU RSES BY DIKING. ADVISE AUTHORITIES IF
DOES ENTER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP
IN COOL, DRY,

WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT &
EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions:AVOID EYE &/OR SKIN CONTACT. INHALATION &/OR
INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR
BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATOR IN CONFINED AREAS.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY WITH
ADEQUATE VENTIL

ATION. MECHANICAL: EXPLOSION PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308 F/155 C

Melt/Freeze Pt:M.P/F.P Text:0 F(-17.8C)

Decomp Temp:Decomp Text:600F,316C

Vapor Pres: