

CHEMRAY COATING CORP -- PAINT, TRAFFIC, HIGHWAY-YELLOW 33538 -- 8010-00-900-3648
===== Product Identification =====

Product ID:PAINT, TRAFFIC, HIGHWAY-YELLOW 33538

MSDS Date:03/12/1990

FSC:8010

NIIN:00-900-3648

MSDS Number: BHVVV

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency

Phone Num:201-245-1111

Preparer's Name:FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

===== Composition/Information on Ingredients =====

Ingred Name:CHROME YELLOW (AS LEAD CHROMATE)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 7.22%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.05 MG/M3

ACGIH TLV:0.05 MG/M3

Ingred Name:MET

HYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 18.93%

Other REC Limits:NONE SPECIFIED

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)

CAS:123-91-1

RTECS #:JG8225000

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 100 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:VMP (ALIPHATIC NAPHTHALENE)

CAS:6472-48-9

Fraction by Wt: 10.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 2.4%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 3.6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA

Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC. 2.07 LBS/GAL OR 248 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION. NERVOUS SYSTEM DEPRESSION.
SKIN, EYE & UPPER RESPIRATORY TRACT IRRIT
ANT. CAN CAUSE DERMATITIS.
CAN ABSORB THROUGH SKIN & CAUSE AUDIT ORY & VESTIBULAR NERVE
DAMAGE.
Explanation of Carcinogenicity:LEAD CHROMATE & 1,4 DIOXANE ARE LISTED
AS CARCINOGENS.
Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED
BY OVER INHALATION. NERVOUS SYSTEM DEPRESSION. SKIN, EYE & UPPER
RESPIRATORY TRACT IRRITANT. CAN ABSORB THROUGH SKIN & CAUSE
AUDITORY & VESTIBULAR NERVE DAMAGE.
Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN

==
=====
===== First Aid Measures =====

First Aid:EYE CONTACT:FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN
CONTACT:REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP &
WATER. INHALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL
PHYSICIAN. INGESTION:DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
F
Flash Point:55.0F,12.8C
Autoignition Temp:Autoignition Temp Text:450F
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS

=====
===== Accidental Release Measures =====

=====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT(SAND, EARTH, SAWDUST) TO SPILL. VENT AREA(OPEN WINDOWS, DOORS). LARGE SPILL: KEEP PRODUCT FROM ENTERING SEWERS/WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF DOES ENTER.

===== Handling and Storage =====

Handling and Storage Precautions: STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT & EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions: AVOID EYE, SKIN CONTACT. INHALATION OR INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS.

Ventilation: LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY WITH ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT

Protecti

ve Gloves: CHEMICAL RESISTANT

Eye Protection: SPLASH GOGGLES OR FACE SHIELDS

Other Protective Equipment: USE CHEMICAL RESISTANT APRON OR CLOTHING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: 162F, 72C

Melt/Freeze Pt: M.P/F.P Text: 0F, -18C

Decomp Temp: Decomp Text: 600F, 316C

Vapor Pres: 45-134 @ 68F

Vapor Density: 4.6

Spec Gravity: 1.66 (H2O=1)

Viscosity: 70-80 @ 77FKREB

Evaporation Rate & Reference: 6.0 (BUTYL ACETATE=1)

Sol

ubility in Water:NEGLIGIBLE

Appearance and Odor:SCHOOL BUS YELLOW WITH PAINT SOLVENT ODOR.

Percent Volatiles by Volume:52.98

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CAN REACT W/OXIDIZING MATERIAL WHEN HEAT TO DECOMP. STRONG ACIDS/BASES,
ALKALIES & REACTIVE METALS(IE SODIUM, POTASSIUM)

Stability Condition to Avoid:HIGH TEMPERATURE & HIGH PRESSURE IN
ALUMINUM SYSTEMS.

Hazardous Decomposition Products:CARBON MONOXIDE,
PHOSGENE &
HYDROCHLORIC ACID, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL
REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL
SITE OR FACILITY. DISPOSE IN CONFORMITY WITH STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The Un
ited States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.