

CHEMRAY COATING CORP -- ENAMEL ALKYD GLOSS (EXT & INT) BLUE 15123 -- 8010-00-853-1859

=====
Product Identification
=====

Product ID:ENAMEL ALKYD GLOSS (EXT & INT) BLUE 15123

MSDS Date:11/03/1988

FSC:8010

NIIN:00-853-1859

MSDS Number: BHWBY

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-111

1

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 48%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:LEAD AS (PB), (LEAD DRIER)

Fraction by Wt: .25%

ACGIH TLV:.05

MG/M3

Ingred Name:VOC=4.06 LBS/GAL OR 487 GRAMS/LITER
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:(ACIGH)(OSHA) 100 PPM (590 MG/M3) FOR 8 HOUR WORK DAY. HIGH VAPOR CONCENTRATIONS (>1000 PPM) ARE IRRITATING TO EYES/RESPIRATORY TRACT. MAY CAUSE HEADACHES & DIZZINESS. PROLONG SKIN CONTACT IRRITATES. REPORTS HAVE ASSOCIATED REPEAT/PROLONG OVEREXPOSUR

E W/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE. MISUSE MAY BE HARMFUL/FATAL

Effects of Overexposure:(ACIGH)(OSHA) 100 PPM (590 MG/M3) FOR 8 HOUR WORK DAY. HIGH VAPOR CONCENTRATIONS (>1000 PPM) ARE IRRITATING TO EYES/RESPIRATORY TRACT. MAY CAUSE HEADACHES & DIZZINESS. PROLONG SKIN CONTACT IRRITATES. REPORTS HAVE ASSOCIATED REPEAT/PROLONG OVEREXPOSURE W/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE. MISUSE MAYBE HARMFUL/FATAL.

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT: REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND WATER. INHAL ATION: IF OVERCOME BY VAPORS REMOVE TO FRESH AIR, CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC

Flash Point:103 F/40 C

Lower Limits:.9

Upper Limit

s:7

Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG OR DRY CHEMICAL.

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS

AND OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP FROM ENTERING SEWERS/WATERCOU RSES BY DIKING. ADVISE AUTHORITIES IF DOES ENTER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS. USE RESPIRATORY PROTECTION AGAINST LEAD DUST DURING SANDING.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60FPM. S

PECIAL: USE ONLY

W/ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:USE CHEM RESISTANT APRON OR CLOTHING TO AVOID REPEATED SKIN CONTACT. SEE OSHA CFR1910.1025 OCCUPATIONAL LEAD EXPOSURE.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE AND KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Supplemental Safety and Health

=====
===== Physical/Chemical P
roperties =====

Boiling Pt:B.P. Text:308F,153C

Melt/Freeze Pt:M.P/F.P Text: