

EASTMAN KODAK COMPANY -- 192 7698,FLEXCOLOR DEVLPR,PART-A(POST 1/90) --
6750-01-050-7789

===== Product Identification =====

Product ID:192 7698,FLEXCOLOR DEVLPR,PART-A(POST 1/90)

MSDS Date:01/04/1990

FSC:6750

NIIN:01-050-7789

MSDS Number: BHWCT

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3

194 FOR MSDS : 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER; WT % RANGE:55-65

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 60.0%

Ingred Name:POTASSIUM CARBONATE; WT % RANGE:25-30

CAS:584

-08-7
RTECS #:TS7750000
Fraction by Wt: 27.5%

Ingred Name:POTASSIUM BICARBONATE; WT % RANGE:5-10%
CAS:298-14-6
Fraction by Wt: 07.5%

Ingred Name:SODIUM SULFITE; WT % RANGE:1-5%
CAS:7757-83-7
RTECS #:WE2150000
Fraction by Wt: 03.00%

Ingred Name:PENIETIC ACID, PENTA SODIUM SALT; WT % RANGE: 1-5%
CAS:140-01-2
Fraction by Wt: 03.00%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:
NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MAY CAUSE EYE IRRITATION.
Explanation of Carcinogenicity:NONE SPECIFIED COMPANY.
Effects of Overexposure:INHALATION: LOW HAZARD FOR USUAL INDUSTRIAL
HANDLING; EYES:CAUSES IRRITATION; SKIN:PROLONGED OR REPEATED
CONTACT MAY CAUSE SKIN IRRITATION; INGESTION: EXPECTED TO BE A LOW
INGESTION HAZARD. IF SWALLOW ED, MAY CAUSE GASTROINTESTINAL TRACT
IRRITATION.
Medical Cond Aggravated by Exposure:NOT STATED BY KODAK.

=====
=== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR; EYES/SKIN:FLUSH WITH LARGE
AMOUNTS OF WATER FOR AT LEAST 15 MINUTE. GET MEDICAL ASSISTANCE IF
SYMPTOMS ARE PRESENT AFTER WASHING; INGESTION: RINSE MOUTH. DRINK
1-2 GLA SSES OF WATER. SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:WEA

R SELF-CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN & EYES.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK W/O RISK.USE PROTECTIVE
EQUIPMENT.DIKE FAR AHEAD WITH SUITABLE ABSORBENT.NEUTRALIZE LIQUID
WITH SODIUM BISULFATE.FLUSH NEUTRALIZED SOLUTION TO SEWER WITH LG
AMTS OF WATER I/A/W RE
GS;SM SPILL (1 PT) MAY BE FLUSHED TO SEWER
W/LG QTY OF H*2O.
Neutralizing Agent:SODIUM BISULFITE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:KEEP AWAY FROM STRONG ACIDS. AVOID CONTACT WITH
SKIN/CLOTHING

===== Exposure Controls/Personal Protection =====

Resp
iratory Protection:IF EXPOSED ABOVE TLV, USE NIOSH/MESA APPROVED
RESPIRATORY PROTECTION.
Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES
Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED CONTACT.
Work Hygienic Practices:GOOD GENERAL HYGEIN PRACTICE RECOMMENDED.
Supplemental Safety and Health
ITEM IS A 3 PARTS KIT; THIS ENTRY DESCRIBES NEWEST FORMULATION OF PART
A EFFECTIVE 1/4/90; SOLUT
ION NO:4802, & ACCESSION NO:427728 OF THIS
PART IS THE SAME AS OLD PRODUCT - SEE PNIND D; SEE PNI A FOR
OLDEST FORMULATION OF THIS PART; ALSO SEE PNI B, C, & E FOR OTHER
PARTS. KEY1:N1

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F/100C
Vapor Pres:18MMHG@20C
Vapor Density:0.6
Spec Gravity:1.409
pH:10.9
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR,COLORLESS SOLUTION;ODORLESS
Percent Volatiles by Volume:60

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID STRONG ACIDS

Stability Condition to Avoid: HEAT, HIGH TEMPERATURES

Hazardous Decomposition Products: NONE SPECIFIED BY THE MANUFACTURER;
HOWEVER EXPECT EMISSION OF OXIDES OF SULFUR AND CARBON ON THERMAL
DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods: NEUTRALIZE WASTE PRODUCT WITH SODIUM BISULFATE &
DISPOSE OF I/A/W THE APPLICABLE FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of
this information to their
particular situation.