

HENTZEN COATINGS INC -- ID 08605 GUA-GD,383 GREEN ZENTHANE -- 8010-01-229-7546

=====
Product Identification
=====

Product ID:ID 08605 GUA-GD,383 GREEN ZENTHANE

MSDS Date:02/08/1990

FSC:8010

NIIN:01-229-7546

MSDS Number: BHXGH

=== Responsible Party ===

Company Name:HENTZEN COATINGS INC

Address:6937 W MILL ROAD

Box:18642

City:MILWAUKEE

State:WI

ZIP:53218-1225

Country:US

Info Phone Num:414-353-4200

/ FAX 414-353-0286

Emergency Phone Num:414-353-4200

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ISOAMYL KETONE

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 29.69%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

Ingred Name:PREPOLYMER OF H

EXAMETHYLENE DIISOCYANATE

Fraction by Wt: 30-40%

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 20-30%

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:COBALT-ZINC SPINEL PIGMENT

Fraction by Wt: 1.0-5.0%

Ingred Name:CHROMIUM (SARA III)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 7.31%

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF735000

0

Fraction by Wt: 1.24%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE)

CAS:822-06-0

RTECS #:MO1740000

Fraction by Wt: 120F OR < 32F. STORE LRG

AMTS IN BLDG DESIGNED TO COMPLY W/OSHA1910.106.KEEP AWAY FROM
SPARKS, OPEN FLAME.KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:IF MOISTURE ENTERS CONTAINERS, PRESSURE CAN BUILD DUE
TO REACTION, PRODUCE CO2, CAN CAUSE SEALED

CONTAINER TO PRESSURIZE
& BURST. DO NOT RESEAL IF CONTAMINATED. DO NOT TAKE INTERNALLY.
CONTAINERS SHOULD BE GROUNDED WHEN POURING. ****

===== Exposure Controls/Personal Protection =====

Respiratory Protection: SURGEON GENERAL REQUIRES AIRLINE RESPIRATORS TO BE USED UNLESS AIR SAMPLING SHOWS EXPOSURE TO BE BELOW OSHA LIMITS. THEN USE EITHER CHEM CARTRIDGE/AIRLINE RESPIRATORS REQUIRED. USE SAME PRECAUTIONS DURING MIXING OR WHERE PAINT FUMES ARE PRESENT

Ventilation:

GEN DILUTION/LOCAL EXHAUST VENT IN VOL/PATTERN TO KEEP AIR CONTAM CONCENT BELOW LIMITS. REMOVE DECOMP PROD WHEN WELD, ETC

Protective Gloves: CHEMICAL RESISTANT GLOVES.

Eye Protection: SAFETY EYEWEAR W/SPLASH GUARDS/SHIELDS

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO KEEP SKIN CONTACT AT MINIMUM. AVOID CONTACT WITH EYES, SKIN & CLOTHING. WASH THOROUGHLY.

Work Hygienic Practices: WASH HANDS & ANY EXPOSED SKIN THOROUGHLY BEFORE EATING OR SMOKING. SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

**** AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. USE W/ADEQUATE VENTILATION & RESPIRATORY EQUIP. EMPTIED CONTAINERS MAY RETAIN HAZARDOUS RESIDUE OR EXPLOSIVE VAPORS. FOLLOW ALL PRECAUTIONS IN THIS DATA SHEET UNTIL CONTAINER IS THOROUGHLY CLEANED OR DESTROYED. **FLUSH AREA W/WATER. REMOVE CONTAINER TO SAFE PLACE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt: B.P. Text: 244 TO 418F

Decomp Temp:

Decomp Text: 400F, 204C

Vapor Pres: 8.00

Vapor Density: > THAN AIR

Spec Gravity: 1.256

Viscosity: 65-68 KREBS

Evaporation Rate & Reference: EQUAL TO BUTYL ACETATE

Solubility in Water: REACTS WITH WATER

Appearance and Odor: OPAQUE LIQUID WITH SOLVENT ODOR.

Percent Volatiles by Volume: 51.43

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

WATER, ALCOHOLS, GLYCOL ETHERS, AMINES.

Stability Condition to Avoid: WATER CONTAMINATION. *(CO2 EVOLVE

D). DON'T

APPLY TO HOT SURFACES. NEVER USE WELD/CUT TORCH ON/NEAR DRUM(EVEN EMPTY DRUM)

Hazardous Decomposition Products:BY FIRE: CO₂, CO, OXIDES OF NITROGEN, TRACES OF HYDROGEN CYANIDE, HEXAMETHYLENE DIISOCYANATE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. INCINERATION IS PREFERRED METHOD OF DISPOSAL.***CARBIDE'S TERGITOL TMN-10 (20%) & WATER (80%).**W/NON-SPARK TOOLS INTO OPEN CONTAINER- ADD MORE NEUTRALIZER & WASH AREA W/NEUTRALIZER **

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and as some responsibility for the suitability of this information to their particular situation.