View NSN Online: https://aerobasegroup.kr/nsn/8010-01-293-6180

## MIDLAND DIVISION DEXTER CORP -- ID 0320T136 HS HARDNER MILC85285 -- 8010-01-293-6180

Product ID:ID 0320T136 HS HARDNER MILC85285

MSDS Date:02/28/1990

FSC:8010

NIIN:01-293-6180

Kit Part:Y

MSDS Number: BHXKK === Responsible Party ===

Company Name: MIDLAND DIVISION DEXTER CORP

Address:31500 HAYMAN ST

City:HAYWARD

State:CA

ZIP:94544-7120

Country:US

Info Phone Num:415-

471-7171

Emergency Phone Num:415-471-7171, 415-791-1961 (NIGHT)

Preparer's Name: CAP

CAGE:98795

=== Contractor Identification ===

Company Name: DEXTER CORP THE DEXTER CROWN METRO AEROSPACE DIV

Address:31500 HAYMAN ST

Box:City:HAYWARD

State:CA

ZIP:94544-7120 Country:US

Phone:510-471-7171

CAGE:98795

======= Composition/Information on Ingredients ========

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 10-20%

Other REC Limits


ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: VOLATILE ORGANIC CONTENT 1.352 POUNDS PER GALLON LESS WATER RTECS #:9999999VO =========== Hazards Identification ========================== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: IRRITANT TO EYES, SKIN AND SKIN SENSITIVITY. MAY AFECT RESPIRATORY TRACT, CENT RAL NERVOUS SYSTEM, ALLERGICE RESPIRATORY AND SKIN REACTION. Effects of Overexposure: OVEREXPOSURE BY INHALATION MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, DIZZINESS, OR DROWSINESS. Medical Cond Aggravated by Exposure: RESPIRATORY PROBLEMS. First Aid:EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. SKIN: REMOVE CONTAMINATED CLOTHING AND WASH SKIN WITH SOAP AND WAT ER. INHALATION: REMOVE FROM EXPOSURE. INGESTION: D RINK WATER. IF NECESSARY, CONSULT A PHYSICIAN FOR ANY OF THESE CONDITIONS. ============ Fire Fighting Measures ========================= Flash Point Method:SCC Flash Point:26.0F,-3.3C Lower Limits: 1.80 Extinguishing Media: USE WATER FOG, FOAM, DRY CHEMICAL, OR CARBON DIOXIDE

:STEL 300 PPM

OSHA PEL:200 PPM/300 STEL

======== Accidental Release Measures ==========

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS



with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.