

CAAP COMPANY, INC. -- CAAPCOAT AS-P108 CATALYST -- 8010-00-459-1756

=====
Product Identification
=====

Product ID:CAAPCOAT AS-P108 CATALYST

MSDS Date:12/24/1988

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: BHXSM

=== Responsible Party ===

Company Name:CAAP COMPANY, INC.

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Info Phone Num:203-468-0055

Emergency Phone Num:203-877-0375

Preparer

's Name:RONALD D. ARENA

CAGE:LO402

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

Company Name:CAAP COMPANY, INC.

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Phone:203-468-0055

CAGE:LO402

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH

TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TRIETHYLENE DIAMINE

CAS:280-57-9

RTECS #:HM0354200

Ingred Name:DIPROPYLENE GLYCOL

CAS:110-98-5

RTECS #:UB8785000

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Re

ports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES; SKIN

IRRITANT. INHALATION RESPIRATORY IRRITANT. CHRONIC:

REPEATED/PROLONGED EXPOSURE MAY CAUSE OF DEFATTING OF SKIN &

DERMATITUS& POSSIBLE SENSITIZATION. INHAL: OF HIGH CONCENTRATIONS

ABOVE TLV'S MAY CAUSE NEURAL IMPAIRMENT.

Effects of Overexposure:BURNING EYES, HEADACHE, DIZZINESS, THROAT

IRRITATION, LOSS OF APPETITE,& NAUSEA CONTACT: MAY CAUSE IRRITATION

OF

SKIN, BURNING OF SKIN OR EYES.

Medical Cond Aggravated by Exposure:PREEXISTING ALLERGIES, ASTHMA, EYE

& SKIN DISORDERMAY BE AGGRAVATED.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH MUCH WATER & CALL PHYSICIAN.

SKIN: WASH WITH SOAP AND WATER, REMOVE

CONTAMINATED CLOTHING. INHAL: REMOVE TO FRESH

AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY & CALL A PHYSICIAN.

INGST: DO NOT INDUCE VOMITING,

CALL A PHYSICIAN

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:27F/-2.22C

Lower Limits:1.0

Upper Limits:7.5

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:USUAL METHODS FOR FLAMMABLE LIQUIDS.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:KEEP IGNITION SOURCES AWAY. CONTAIN
W/ABSORBANT MATERIAL. USE PROTECTIVE EQUIPMENT. CLEAN
UP

ABSORBANT AND CONTAIN SECURELY. SWEEP & WET MOP WITH SOAP AND
WATER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IGNITION SOURCES AWAY. KEEP
CLOSED WHEN NOT IN USE. KEEP AREA CLEAN. STORE BELOW 100F.

Other Precautions:AVOID CONTACT WITH SKIN, EYES, AND CLOTHING. IF
SPRAYING, DO NOT BREATHE MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR CANNISTER
MASK OR S.C.B.A. FOR
EMERGENCIES

Ventilation:LOCAL EXHAUST PREFERRED; SPECIAL SPRAY BOOTH IS RECOMMENDED
FOR SPRAY; MECHANICAL ACCEPTABLE

Protective Gloves:NEOPRENE OR POLYETHYLENE

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:RUBBER OR POLYETHYLENE APRON. RUBBER BOOTS
FOR SPILLS

Work Hygienic Practices:WASH W/SOAP & WATER AFTER HANDLING. CONTACT
LENSES NOT RECOMMENDED FOR SOLVENTS SINCE EYE INJURY MAY
RESULT.

Supplemental Safety and Health

KEY1:F3. KIT CONSIST

S OF EIGHT PARTS. PART ONE HAS PNI A, PART TWO HAS PNI B, PART THREE HAS PNI C ... THROUGH PNI H, SAME NSN.

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:238-291F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:15

Vapor Density:3.5

Spec Gravity:0.866

Evaporation Rate & Reference:0.96

Solubility in Water:PARTIAL

Appearance and Odor:CLEAR COLORLESS LIQUID WITH AROMATIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:IGNITION SOURCES, HOT SURFACES, AND TEMPERATURES ABOVE 100F

Hazardous Decomposition Products:UNDER FIRE CONDITIONS, OXIDES OF CARBON & NITROGEN,POSSIBLEHCN AS WITH MANY NITROGEN COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION PREFERRED. RCRA HAZARDOUS IGNITABLE WASTE. DISPOSE OF ACCORDING TO FEDERAL, STATE, ANDLOCAL

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.