

CAAP COMPANY, INC. -- CHEMGLAZE 9924, WASH PRIMER, PART A -- 8010-00-459-1756

=====  
Product Identification  
=====

Product ID:CHEMGLAZE 9924, WASH PRIMER, PART A

MSDS Date:09/12/1988

FSC:8010

NIIN:00-459-1756

Kit Part:Y

MSDS Number: BHXSN

=== Responsible Party ===

Company Name:CAAP COMPANY, INC.

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Info Phone Num:203-468-0055

Emergency Phone Num:2

03-877-0375

Preparer's Name:RONALD D. ARENA

CAGE:LO402

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

Company Name:CAAP COMPANY, INC.

Box:2066

City:HUNTINGTON

State:CT

ZIP:06484

Country:US

Phone:203-468-0055

CAGE:LO402

Company Name:LORD CORPORATION, CHEMICAL PRODUCTS DIVISION

Address:2000 WEST GRANDVIEW BLVD

Box:City:ERIE

State:PA

ZIP:16514-0038

Country:US

Phone:814-868-3611

CAGE:3

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 15%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 10%

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 1%

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

E

PA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SEC-BUTYL ALCOHOL

(VAPOR PRESSURE 13 MMHG @ 20C)

CAS:78-92-2

Fraction by Wt: 15%

OSHA PEL:150 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE

(VAPOR PRESSURE 3.7 MMHG @ 20C)

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 30%

OSHA PEL:NA

ACGIH TLV:NA

Ingred Name:DIPROPYLENE GLYCOL METHYL ETHER ACETATE

(VAPOR PRESSURE AIR

Evaporation Rate &amp; Reference:SLOWER THAN ETHE

R

Solubility in Water: SOLUBLE

Appearance and Odor: RED VISCOUS LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume: 77

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG ACIDS

Stability Condition to Avoid: HIGH TEMPERATURES, OPEN FLAMES, SPARKS

Hazardous Decomposition Products: CARBON DIOXIDE/MONOXIDE, PHENOL VAPORS, OXIDES OF NITROGEN

===== Disposal Considerations =====

=

Waste Disposal Methods: DISPOSAL IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD CAUTION INFORMATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.