View NSN Online: https://aerobasegroup.kr/nsn/6810-00-805-9798

Product ID:CYCLOHEXYLAMINE MSDS Date:02/22/1995 FSC:6810 NIIN:00-805-9798 MSDS Number: BHXTJ === Responsible Party === Company Name: VAN WATERS AND ROGERS INC., UNIVAR CORP. Address: INVALID INFO. PER COMPANY USE 0STM5 Box:5932 City:SEATTLE State:WA ZIP:98104-1564 Country:US Info Phone Num:206-447-5911 Emergency Phone Num:206-447-5911 CAGE:87664 === Contractor Identification === Company Name: CHEMICAL COMMODITIES AGENCY, INC. Address:27447 PACIFIC STREET Box:City:HIGHLAND State:CA ZIP:92346-2640 Country:US Phone:909-864-2310 CAGE:60777 Company Name: VAN WATERS AND ROGERS INC., UNIVAR CORP. Address:1600 NORTON BLDG. 801 2ND AVENUE Box:City:SEATTLE State:WA ZIP:98104-1564 Country:US Phone:206-447-5911/800-424-9300(CHEMTREC) CAGE:87664 Company Name: VOPAK USA INC Address:6100 CARILL

ON POINT Box:City:KIRKLAND State:WA ZIP:98033-7357 Country:US Phone:425-889-3400/425-889-3617 CAGE:0STM5

======= Composition/Information on Ingredients ==========

Ingred Name:CYCLOHEXYLAMINE (SARA 302) CAS:108-91-8 RTECS #:GX0700000 Fraction by Wt: 99% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM ACGIH TLV:10 PPM; 9596

Ingred Name:CYCLOHEXANOL CAS:108-93-0 RTECS #:GV7875000 Fraction by Wt: 0.1% Other REC Limits:NONE RECOMMENDED OSHA PEL:S, 50 PPM ACGIH TLV:S, 50 PPM; 9596

===

LD50 LC50 Mixture:LD50 ORAL RAT = 11 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:CORROSIVE TO EYES AND SKIN. MAY CAUSE PERMANENT EYE DAMAGE AND BLINDNESS. MAY CAUSE SKIN SENSITIZATION. AFFECTS THE CENTRAL NERVOUS SYSTEM. SWALLOWING LARGE QUANTITIES CAN CAUSE DEATH. CHRONIC EFFECTS :DESTRUCTION OF SKIN TISSUES OR

PRIMARYIRRITANT DERMATITIS.INHALATION MAY CAUSE DAMAGE TO AFFECTED TISSUES.

Effects of Overexposure:EYES:SEVERELY IRRITATING. SKIN:SEVERE IRRITATION AND BURNS. INHALATION:IRRITATION TO RESPIRATORY TRACT, LIGHT-HEADEDNESS, DROWSINESS, ANXIETY, NAUSEA, AND VOMITING. INGESTION:BURNS, SEVERE ABDOMINAL P AIN, NAUSEA, VOMITING, COLLAPSE, DEATH.

Medical Cond Aggravated by Exposure: INDIVIDUALS WITH A HISTORY OF SKIN OR RESPIRATORY ILLNESSES MAY BE MORE ADVERSELY AFFECTE.

=====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.SEE DOCTOR. SKIN:REMOVE CONTAMINATED CLOTHING AND SHOES. WASH WITH SOAP AND WATER.SEE DOCTOR. INHALATION: REMOVE VICTIM TO FRESH AIR.GIVE OXYGEN/CPR IF NEEDED.SEE DOCTOR. INGESTION:GIVE LARGEAMOUNTS OF WATER OR MILK.DO NOT INDUCE VOMIT.NOTHING BY MOUTH IF UNCONSCIOUS.SEE DOCTOR.

Flash

Point Method:CC

Flash Point:83.0F,28.3C Lower Limits:0.66

Upper Limits:8.2

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. DO NOT USE WATER TO FIGHT FIRE.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard: AVOID WATER BECAUSE PRODUCT WILL FLOAT ON WATER AND MAY REIGNITE. VAPORS HEAVIER THAN AIR.MAY TRA

VEL A LONG

DISTANCE ALONG GROUND AND FLASHBACK.

Spill Release Procedures: ELIMINATE IGNITION SOURCES. VENTILATE AREA.WEAR EYE PROTECTION, RESPIRATOR OR SCBA, FULL PROTECTIVE CLOTHING.USE NON-SPARKING TOOLS.STOP LEAK.ABS0RB IN INERT ABSORBENT AND PLACE INTO APPROPIATE DISPOSAL CONTAINER AND SEAL.

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED

PLACE, AWAY FROM HEAT, IGNITION SOURCES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:VENT CONTAINERS FREQUENTLY,AND MORE OFTEN IN WARM WEATHER,TO RELIEVE PRESSURE.ELECTRICALLY GROUND ALL EQUIPMENT.DO NOT USE PRESSURE TO EMPTY CONTAINER.DO NOT CUT,WELD,GRIND,DRILL NEAR CONTAINER.DO NOT GET IN EYES, SKIN OR ON CLOTHING.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH/MSHA

RESPIRATOR WITH ORGANIC VAPORS CARTRIDGE APPROPIATE FOR EXPOSURE OF CONCERN OR SCBA IF TLV IS EXCEEDED. Ventilation:SUFFICIENT MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV. Protective Gloves: RUBBER Eye Protection: CHEMICAL GOGGLES AND FULL FACESHIELD. Other Protective Equipment: FULL WORK CLOTHING, RUBBER APRON & BOOTS TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER Work Hygienic Practices: AVOID CONTACT WIT **H EYES & SKIN.DO NOT BREATHE** VAPORS.WASH THOROUGHLY AFTER HANDLING.LAUNDER CONTAMINATED CLOTHING. Supplemental Safety and Health NONE NOTED.

HCC:F7 Boiling Pt:B.P. Text:135F,57C Melt/Freeze Pt:M.P/F.P Text:0F,-18C Vapor Pres:11 Vapor Density:3.42 Spec Gravity:0.867 Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID, STRONG FISHY ODOR.

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS, ACIDS, ALL COPPER ALLOYS, LEAD. Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS. EMPTY CONTAINERS CAN HAVE RESIDUES,AND ARE SUBJEC

T TO PROPER WASTE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informa tion to their

particular situation.