View NSN Online: https://aerobasegroup.kr/nsn/3439-00-262-4229

ARCAIR COMPANY INC.SUBS.OF AIR PRODUCTS & CHEMICAL -- AIR CARBON ARC ELECTRODES

-- 3439-00-262-4229

Product ID:AIR CARBON ARC ELECTRODES

MSDS Date:07/01/1989

FSC:3439

NIIN:00-262-4229

MSDS Number: BHXYB === Responsible Party ===

Company Name: ARCAIR COMPANY INC. SUBS. OF AIR PRODUCTS & CHEMICAL

Address:4200 WEST HARRY ST

Box:12250 City:WICHITA State:KS ZIP:67277

Cou

ntry:US

Info Phone Num:316-942-1421

Emergency Phone Num:316-942-1421

Preparer's Name: OPERATIONS DEPARTMENT

CAGE:KO945

=== Contractor Identification ===

Company Name: ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC

Address:4200 WEST HARRY ST

Box:12250 City:WICHITA State:KS ZIP:67277 Country:US

Phone:316-942-1421

CAGE:09687

Company Name: ARCAIR COMPANY INC. SUBS. OF AIR PRODUCTS & CHEMICAL

Address:4200 WEST HARRY ST

Box:12250 City:WICHITA State:KS ZIP:67277

Phone:316-942-1421

CAGE:KO945

Country:US

==

====== Composition/Information on Ingredients ========

Ingred Name: GRAPHITE, SYNTHETIC

CAS:7440-44-0

RTECS #:FF5250100 Fraction by Wt: 20-80%

Other REC Limits: NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name: GRAPHITE, NATURAL

CAS:7782-42-5

RTECS #:MD9659600 Fraction by Wt: 20-80%

Other REC Limits: NONE SPECIFIED

OSHA PEL:15 MPPCF RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name: COPPER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000 Fraction by Wt: 10-30%

Other REC Limits:NONE SPECIFIED OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: BAKED

Other REC Limits: NONE SPECIFIED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

=========== Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chron

ic:FUMES AND GASES CAN BE DANGEROUS TO
YOUR HEALTH. ARC RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK
CAN KILL.

Effects of Overexposure:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE AND THROAT. CHRONIC:EXCESSIVE LEVELS MAY CAUSE BRONQUIAL ASTHMA,LUNG FIBROSIS AND PNEUMOCONIOSIS. EXPOSUR E TO ULTRAVIOLET LIGHT CAN CAUSE INFLAMMATION, BLURRED VISION, HEADACHE, "SUNBURN".

Medical Cond Aggravated by Exposure: AGGRAVATION OF

EXISTING RESPIRATORY

OR ALLERGIC CONDITIONS, ERYTHMAS. HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG SMOKERS.

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION. IF NOT BREATHING, GIVE CPR/OXYGEN. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS. TREAT UV EXPOSURE SIMILAR TO SUNBURN, SEE DOCT OR.

============= Fire Fighting Measures ========================

Extinguishing

Media: AS APPROPIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard: FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

	 Accidental 	Release	Measures	
--	--------------------------------	---------	----------	--

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PL

ACE IN APPROPIATE DISPOSAL CONTAINER.

============= Handling and Storage ==========================

Handling and Storage Precautions:STORE IN DRY AREA. ELECTRODES EXPOSED TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING AT 300F FOR TEN HOURS.

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES.MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES.AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA. WELDING ARC CAN IGNITE COMBUSTIBLES AND FLAMMABLE

=========	Exposure	Controls/Personal Protection	=========
-----------	----------	------------------------------	-----------

Respiratory Protection: FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO KEEP BELOW TLV.

Protective Gloves: WELDER'S GLOVES.

Eye Protection: HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH, ARM

PROTECTOR, APRON, HAT AND SHOULDER PROTECTION. AIR SAMPLING TO DETERMINE CORRECTIVE

MEASURES.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKING OR USING SANITARY FACILITIES. AVOID ELECTRICAL SHOCK AND UV EXPOSURE.

Supplemental Safety and Health

NONE.

	Physical/Chemical Properties	S =========
--	------------------------------	-------------

HCC:N1

Solubility in Water: INSOLUBLE

Appearance and Odor:SOLID, NOT NOTABLE ODOR, COPPER COATED BLACK ROD.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

NONE.

Stability Cond

ition to Avoid:NONE.

Hazardous Decomposition Products:FUMES OF METALS AND METAL OXIDES FROM ELECTRODE AND BASE METAL, CARBON MONOXIDE, CARBON DIOXIDE, OZONE, NITROGEN OXIDES.

======= Disposal Considerations ===========

Waste Disposal Methods:CONSULT WITH YOUR LOCAL ENVIRONMENTAL OFFICER.DISPOSE OF FUMES,FLUX OR WELD GRINDING RESIDUE FROM THE WORK AREA OR FROM FILTERS IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (

provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.