

DOW CORNING CORPORATION -- DOW CORNING (R) S CATALYST -- 8030-00-965-6704

=====
Product Identification
=====

Product ID:DOW CORNING (R) S CATALYST

MSDS Date:10/04/1985

FSC:8030

NIIN:00-965-6704

Kit Part:Y

MSDS Number: BHYKV

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-5900

Emergency Phon

e Num:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:DIBUTYL TIN DILAURATE

(REGISTERED TRADEMARK OF DOW CORNING CORP & CATALYST)

CAS:77-58-7

RTECS #:WH7000000

Fraction by Wt: 5%

OSHA PEL:0.1 MG/M3

ACGIH TLV:.01 MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:NO KNOWN ADVERSE CHRONIC HLTH EFFECTS,
BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED. THIS
PRODUCT MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN
PEOPLE.INGST: SUBST

ANTIAL AMOUNTS MAY CAUSE SOME INJURY.

Effects of Overexposure:EYE:MAY IRRIT. SERIOUSLY W/MOD. CORNEA INJURY &
CONSIDBL REDNESS LASTING A WEEK SKIN: SGL EXPSR FOR SEVRL HRS MAY
CAUSE SLIGHT REDING.LONGER/REPTD CONTC MAY CAUSE MOD IRRIT/POSS.
A MLD BURN & INJURY DUE TO ABSORB.;INHAL:NO IRRIT. TO NOSE OR
THROAT EXPECTED.;INGST:AMNT BY FINGERS TO MOUTH SHOULD NOT CAUSE
INJURY.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER

R FOR 15 MINUTES

SKIN: WIPE OFF AND FLUSH WITH WATER. OBTAIN

IMMEDIATE MEDICAL ATTENTION. INHAL: NO PROBLEMINGST: OBTAIN

IMMEDIATE MEDICAL ATTENTION

=====
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>250F/121C

Lower Limits:ND

Upper Limits:ND

Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM, AND OTHER

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND

PROTECTIVE CLOTHING SHOULD BE WORN IN F

IGHTING FIRES INVOLVING
CHEMICALS

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 90F/32C. USE REASONABLE
CARE & CAUTION

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAP
OR TYPE

Ventilation:MECHANICAL RECOMMENDED

Eye Protection:SAFETY GLASSES/CHEMICAL GOGGLES

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING

Supplemental Safety and Health

IF A SPLASH OCCURS, CHANGE CONTAMINATED CLOTHING AS SOON AS POSSIBLE &
THOROUGH-LY FLUSH AFFECTED AREAS WITH COOL WATER. THESE PRECAUTIONS
ARE FOR ROOM TEMP. HANDLING; USE AT ELEVATED TEMP. MAY REQU IRE
ADDED PRECAUTIONS.

===== Physical/Chemical Properties =====

HCC:B3

B

Boiling Pt:B.P. Text:>300F/149C

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres: