

CHEMRAY COATINGS, CORP. -- PRIMER, ZINC CHROMATE YELLOW ALKYD TYPE --
8010-00-161-7419

=====
===== Product Identification =====

Product ID:PRIMER, ZINC CHROMATE YELLOW ALKYD TYPE

MSDS Date:09/11/1989

FSC:8010

NIIN:00-161-7419

MSDS Number: BJDJG

=== Responsible Party ===

Company Name:CHEMRAY COATINGS, CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:2

01-245-1111

Emergency Phone Num:201-245-1111

Preparer's Name:FRED ARMSTRONG

CAGE:OBRN9

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

Company Name:CHEMRAY COATINGS CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:800-924-9300

CAGE:OBRN9

=====
===== Composition/Information on Ingredients =====

Ingred Name:STODDAR

D SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 32%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:ZINC CHROMATE
CAS:50922-29-7
RTECS #:GB3295000
Fraction by Wt: 23%
ACGIH TLV:0.01 MG/M3

Ingred Name:LEAD DRIER AS (PB)
Fraction by Wt: 0.1%
OSHA PEL:0.05 MG/M3
ACGIH TLV:0.15 MG/M3

Ingred Name:COLBALT DRIER AS (CO)
Fraction by Wt: 0.03%
OSHA PEL:0.01 MG/M3
ACGIH TLV:0.01 MG/M3

Ingred Name:VOC. ORGANIC CMPD 3.6 LB/GAL LESS WATER & NPRS* 432 G/L
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION.
Explanation of Carcinogenicity:CHROMATES ARE CARCINOGENS
Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED
BY OVER INHALATION.
Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL A PHYSICIAN. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND
WATER. INH ALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL
A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL A
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method

:SCC
Flash Point:103F/40C
Autoignition Temp:Autoignition Temp Text:473F
Lower Limits:0.9
Upper Limits:7

Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL.
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL
ENCLOSED CONTAINERS WITH WATER SPRAY.AVOID BREATHING VAPORS OR
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT,
SPARK& OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST)TO SPILL.
VENTILATE AREA (OPEN WINDOWS, DOORS) IF LARGE SPILL KEEP PRODUCT
FROM ENTERING SEWER/WATER COURSES BY DIKING. ADVISE AUTHORITIES IF
ENTERED.
Neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES, KEEP
IN COOL, DRY, WELL VENTILAT
ED AREAS. AVOID DIRECT SUNLIGHT AND
EXTREME TEMPERATURES, HOT OR COLD.
Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF
MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING
DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATOR IN CONFINED AREA.
Ventilation:LOCAL EXHAUST-FACE VELOCITY 60 FPM. SPECIAL USE ONLY WITH
ADEQUATE VENTILATION. MECHANICAL U
SE EXPLOSION PROOF EQUIPMNT.
Protective Gloves:CHEMICAL RESISTANT
Eye Protection:SPLASH GOGGLES OR FACE SHIELD
Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING
Supplemental Safety and Health
AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF MISTS, SPRAY OR
VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:308F/155C
Melt/Freeze Pt:M.P/F.P Text:0F(-17.8C)
Decomp Temp:Decomp Text:600

F/316C
Vapor Pres: