View NSN Online: https://aerobasegroup.kr/nsn/4920-00-870-0582

KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS -- NITROGEN A800500-10 -- 4920-00-870-0582

Product ID:NITROGEN A800500-10 MSDS Date:05/20/1986 FSC:4920 NIIN:00-870-0582 **MSDS Number: BJDTH** === Responsible Party === Company Name: KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS Address:2500 AIRPORT DRIVE City:WILSON State:NC ZIP:27893-9604 Country:US Info Phone Num:307-744-5487 Emergency Phone Num:919-237-7004 CAGE:61423 === Contractor Identification === Company Name: KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS Address:2500 AIRPORT DRIVE Box:City:WILSON State:NC ZIP:27893-9604 Country:US Phone:252-237-7004 CAGE:61423

Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Fraction by Wt: 100% ACGIH TLV:ASPHYXIANT; 9192

LD50 LC50 Mixtur

OXYGEN. FLUSH EYES W/WATER AT LEAST 15 MIN. FOR EXPOSURE TO LIQUID, WARM FROSTBITE AREA WITH WATER (NOT TO EXCEED 105F). IN CASE OF MASSIVE EXPOSURE, REMOVE CLOTHES AND SHOWER W/WARM WATER. NOTE: THERE IS NO SPECIFIC ANTIDOTE. DIR. TREATMENT AT CNTRL OF SYMPTOM.

Extinguishing Media:NITROGEN CANNOT CATCH FIRE Fire Fighting Procedures:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.EVACUATE PERSONNEL FROM DANGER AREA.DELUGE CONTAINER W/WATER SPRAY FROM MAX.DISTANCE TIL COOL.MOVE CONTAINERS AWAY. Unusual Fire/Explosion Hazard:GAS CANNOT CATCH FIRE.CONT.MAY RUPTURE DUE TO HEAT OR FIRE.NO PART OF A CONT.SHOULD BE >52C.MOST CONTAINERS WILL VENT CON TENTS WHEN EXPOSED TO HIGH TEMPS.

Spill Release Procedures:EVACUATE PERSONNEL. USE SCBA WHERE NEEDED. VENTILATE AREA WHERE LEAK OCCURED. TEST AREA FOR SUFFICIENT OXYGEN PRIOR TO PERMITTING RE-ENTRY OF PERSONNEL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE & USE W/ADEQUATE VENTILATIONS. MIXING TWO OR M ORE GASES OR LIQUIDIFIED GASES MAY COMBINE TO CREATE UNEXPECTED HAZARD.OBTAIN SAFETY INFORMATION. Other Precautions: NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN THE SYSTEM BY VENTING TO A SAFE PLACE, THEN REPAIR THE LEAK. Respiratory Protection: PER OSHA 29 CFR 1910.134 - ACCEPTABLE TO MSHA AND NIOSH Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL ACCEPTABLE Protectiv e Gloves: USE FOR HANDLING CYLINDERS & 1910.132. Eye Protection: I/A/W OSHA CFR 1910.133 Other Protective Equipment: METATORSAL SHOES FOR CYLINDER HANDLING, IAW OSHA 29 CFR 1910.132 Work Hygienic Practices: GOOD HYGIENE PRACTICE AS WITH ANY INDUSTRIAL CHEMICAL Supplemental Safety and Health THIS IS PART "B" OF A TWO PART PRODUCT, WHICH IS NOT A KIT.

Boiling Pt:B.P. Text:-320F,-195C Melt/Freeze Pt:M.P/F.P Text:-346F,-210C Vapor Pres: @ 20C GAS Vapor Density:0.967 Spec Gravity:1.2506G/L @ 0C Solubility in Water:SLIGHT Appearance and Odor:COLORLESS,ODORLESS GAS AT AMBIENT TEMP AND PRESSURE

Stability Indicator/Materials to Avoid:YES UNDER CERTAIN CONDITIONS NITROGEN CAN REACT VIOLENTLY W/LITHIUM,NEODYMIUM,TITANIUM OR OZONE. Stability Condition to Avoid:CAUTION HIGH PRESSURE GAS Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

=

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE. DISCARD ANY PRODUCT, RESIDUE DISPOSABLE CONTAINERS OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER I/A/W FED, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or

implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.